API Reference

Amazon Managed Service for Apache Flink (formerly Amazon Kinesis Data Analytics for Apache Flink)

API Version 2018-05-23

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Managed Service for Apache Flink (formerly Amazon Kinesis Data Analytics for Apache Flink): API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Services or capabilities described in AWS documentation might vary by Region. To see the differences applicable to the AWS European Sovereign Cloud Region, see the AWS European Sovereign Cloud User Guide.

Table of Contents

Welcome **1**
Actions **2**
AddApplicationCloudWatchLoggingOption 4
Request Syntax 4
Request Parameters 4
Response Syntax 5
Response Elements 5
Errors 6
See Also 7
AddApplicationInput 9
Request Syntax 9
Request Parameters 10
Response Syntax 11
Response Elements 12
Errors 13
See Also 14
AddApplicationInputProcessingConfiguration 15
Request Syntax 15
Request Parameters 15
Response Syntax 16
Response Elements 16
Errors 17
See Also 18
AddApplicationOutput 20
Request Syntax 20
Request Parameters 21
Response Syntax 21
Response Elements 22
Errors 23
See Also 24
AddApplicationReferenceDataSource 25
Request Syntax 25
Request Parameters 26
Response Syntax 27

Response Elements 27
Errors 28
See Also 29
AddApplicationVpcConfiguration 30
Request Syntax 30
Request Parameters 30
Response Syntax 31
Response Elements 32
Errors 33
See Also 33
CreateApplication 35
Request Syntax 35
Request Parameters 39
Response Syntax 41
Response Elements 47
Errors 47
See Also 48
CreateApplicationPresignedUrl 50
Request Syntax 50
Request Parameters 50
Response Syntax 51
Response Elements 51
Errors 52
See Also 52
CreateApplicationSnapshot 53
Request Syntax 53
Request Parameters 53
Response Elements 53
Errors 54
See Also 55
DeleteApplication 56
Request Syntax 56
Request Parameters 56
Response Elements 56
Errors 57
See Also 57

DeleteApplicationCloudWatchLoggingOption 59
Request Syntax 59
Request Parameters 59
Response Syntax 60
Response Elements 61
Errors 61
See Also 62
DeleteApplicationInputProcessingConfiguration 64
Request Syntax 64
Request Parameters 64
Response Syntax 65
Response Elements 65
Errors 66
See Also 66
DeleteApplicationOutput 68
Request Syntax 68
Request Parameters 68
Response Syntax 69
Response Elements 69
Errors 70
See Also 70
DeleteApplicationReferenceDataSource 72
Request Syntax 72
Request Parameters 72
Response Syntax 73
Response Elements 73
Errors 74
See Also 74
DeleteApplicationSnapshot 76
Request Syntax 76
Request Parameters 76
Response Elements 77
Errors 77
See Also 78
DeleteApplicationVpcConfiguration 79
Request Syntax 79

Request Parameters 79
Response Syntax 80
Response Elements 80
Errors 81
See Also 82
DescribeApplication 83
Request Syntax 83
Request Parameters 83
Response Syntax 83
Response Elements 89
Errors 89
See Also 90
DescribeApplicationOperation 91
Request Syntax 91
Request Parameters 91
Response Syntax 92
Response Elements 92
Errors 92
See Also 93
DescribeApplicationSnapshot 94
Request Syntax 94
Request Parameters 94
Response Syntax 94
Response Elements 95
Errors 95
See Also 96
DescribeApplicationVersion 97
Request Syntax 97
Request Parameters 97
Response Syntax 98
Response Elements 103
Errors 103
See Also 104
DiscoverInputSchema 105
Request Syntax 105
Request Parameters 105

Response Syntax 106
Response Elements 107
Errors 108
See Also 109
ListApplicationOperations 111
Request Syntax 111
Request Parameters 111
Response Syntax 112
Response Elements 113
Errors 113
See Also 114
ListApplications 115
Request Syntax 115
Request Parameters 115
Response Syntax 116
Response Elements 116
Errors 117
See Also 117
ListApplicationSnapshots 118
Request Syntax 118
Request Parameters 118
Response Syntax 119
Response Elements 119
Errors 120
See Also 120
ListApplicationVersions 121
Request Syntax 121
Request Parameters 121
Response Syntax 122
Response Elements 122
Errors 123
See Also 123
ListTagsForResource 125
Request Syntax 125
Request Parameters 125
Response Syntax 125

Response Elements 125
Errors 126
See Also 126
RollbackApplication 128
Request Syntax 128
Request Parameters 128
Response Syntax 129
Response Elements 134
Errors 135
See Also 135
StartApplication 137
Request Syntax 137
Request Parameters 137
Response Syntax 138
Response Elements 138
Errors 138
See Also 139
StopApplication 140
Request Syntax 140
Request Parameters 140
Response Syntax 141
Response Elements 141
Errors 142
See Also 142
TagResource 144
Request Syntax 144
Request Parameters 144
Response Elements 145
Errors 145
See Also 145
UntagResource 147
Request Syntax 147
Request Parameters 147
Response Elements 147
Errors 148
See Also 148

UpdateApplication 150
Request Syntax 150
Request Parameters 155
Response Syntax 157
Response Elements 162
Errors 163
See Also 164
UpdateApplicationMaintenanceConfiguration 165
Request Syntax 165
Request Parameters 165
Response Syntax 166
Response Elements 166
Errors 167
See Also 167
Data Types 169
ApplicationCodeConfiguration 174
Contents 174
See Also 174
ApplicationCodeConfigurationDescription 175
Contents 175
See Also 175
ApplicationCodeConfigurationUpdate 176
Contents 176
See Also 176
ApplicationConfiguration 177
Contents 177
See Also 178
ApplicationConfigurationDescription 179
Contents 179
See Also 180
ApplicationConfigurationUpdate 182
Contents 182
See Also 183
ApplicationDetail 184
Contents 184
See Also 188

ApplicationEncryptionConfiguration 189
Contents 189
See Also 189
ApplicationEncryptionConfigurationDescription 190
Contents 190
See Also 190
ApplicationEncryptionConfigurationUpdate 191
Contents 191
See Also 191
ApplicationMaintenanceConfigurationDescription 192
Contents 192
See Also 192
ApplicationMaintenanceConfigurationUpdate 193
Contents 193
See Also 193
ApplicationOperationInfo 194
Contents 194
See Also 195
ApplicationOperationInfoDetails 196
Contents 196
See Also 197
ApplicationRestoreConfiguration 198
Contents 198
See Also 198
ApplicationSnapshotConfiguration 200
Contents 200
See Also 200
ApplicationSnapshotConfigurationDescription 201
Contents 201
See Also 201
ApplicationSnapshotConfigurationUpdate 202
Contents 202
See Also 202
ApplicationSummary 203
Contents 203
See Also 204

ApplicationSystemRollbackConfiguration 205
Contents 205
See Also 205
ApplicationSystemRollbackConfigurationDescription 206
Contents 206
See Also 206
ApplicationSystemRollbackConfigurationUpdate 207
Contents 207
See Also 207
ApplicationVersionChangeDetails 208
Contents 208
See Also 208
ApplicationVersionSummary 209
Contents 209
See Also 209
CatalogConfiguration 210
Contents 210
See Also 210
CatalogConfigurationDescription 211
Contents 211
See Also 211
CatalogConfigurationUpdate 212
Contents 212
See Also 212
CheckpointConfiguration 213
Contents 213
See Also 215
CheckpointConfigurationDescription 216
Contents 216
See Also 217
CheckpointConfigurationUpdate 219
Contents 219
See Also 221
CloudWatchLoggingOption 222
Contents 222
See Also 222

CloudWatchLoggingOptionDescription 223
Contents 223
See Also 224
CloudWatchLoggingOptionUpdate 225
Contents 225
See Also 225
CodeContent 226
Contents 226
See Also 226
CodeContentDescription 228
Contents 228
See Also 229
CodeContentUpdate 230
Contents 230
See Also 230
CSVMappingParameters 232
Contents 232
See Also 232
CustomArtifactConfiguration 234
Contents 234
See Also 234
CustomArtifactConfigurationDescription 236
Contents 236
See Also 236
DeployAsApplicationConfiguration 238
Contents 238
See Also 238
DeployAsApplicationConfigurationDescription 239
Contents 239
See Also 239
DeployAsApplicationConfigurationUpdate 240
Contents 240
See Also 240
DestinationSchema 241
Contents 241
See Also 241

EnvironmentProperties 242
Contents 242
See Also 242
EnvironmentPropertyDescriptions 243
Contents 243
See Also 243
EnvironmentPropertyUpdates 244
Contents 244
See Also 244
ErrorInfo 245
Contents 245
See Also 245
FlinkApplicationConfiguration 246
Contents 246
See Also 246
FlinkApplicationConfigurationDescription 248
Contents 248
See Also 249
FlinkApplicationConfigurationUpdate 250
Contents 250
See Also 250
FlinkRunConfiguration 252
Contents 252
See Also 252
GlueDataCatalogConfiguration 253
Contents 253
See Also 253
GlueDataCatalogConfigurationDescription 254
Contents 254
See Also 254
GlueDataCatalogConfigurationUpdate 255
Contents 255
See Also 255
Input 256
Contents 256
See Also 257

InputDescription 258
Contents 258
See Also 260
InputLambdaProcessor 261
Contents 261
See Also 261
InputLambdaProcessorDescription 262
Contents 262
See Also 263
InputLambdaProcessorUpdate 264
Contents 264
See Also 264
InputParallelism 265
Contents 265
See Also 265
InputParallelismUpdate 266
Contents 266
See Also 266
InputProcessingConfiguration 267
Contents 267
See Also 267
InputProcessingConfigurationDescription 268
Contents 268
See Also 268
InputProcessingConfigurationUpdate 269
Contents 269
See Also 269
InputSchemaUpdate 270
Contents 270
See Also 270
InputStartingPositionConfiguration 272
Contents 272
See Also 272
InputUpdate 273
Contents 273
See Also 274

JSONMappingParameters 275
Contents 275
See Also 275
KinesisFirehoseInput 276
Contents 276
See Also 276
KinesisFirehoseInputDescription 277
Contents 277
See Also 277
KinesisFirehoseInputUpdate 279
Contents 279
See Also 279
KinesisFirehoseOutput 280
Contents 280
See Also 280
KinesisFirehoseOutputDescription 281
Contents 281
See Also 281
KinesisFirehoseOutputUpdate 283
Contents 283
See Also 283
KinesisStreamsInput 284
Contents 284
See Also 284
KinesisStreamsInputDescription 285
Contents 285
See Also 285
KinesisStreamsInputUpdate 287
Contents 287
See Also 287
KinesisStreamsOutput 288
Contents 288
See Also 288
KinesisStreamsOutputDescription 289
Contents 289
See Also 289

KinesisStreamsOutputUpdate 291
Contents 291
See Also 291
LambdaOutput 292
Contents 292
See Also 292
LambdaOutputDescription 293
Contents 293
See Also 293
LambdaOutputUpdate 295
Contents 295
See Also 295
MappingParameters 296
Contents 296
See Also 296
MavenReference 297
Contents 297
See Also 298
MonitoringConfiguration 299
Contents 299
See Also 299
MonitoringConfigurationDescription 301
Contents 301
See Also 301
MonitoringConfigurationUpdate 303
Contents 303
See Also 303
OperationFailureDetails 305
Contents 305
See Also 305
Output 306
Contents 306
See Also 307
OutputDescription 308
Contents 308
See Also 309

OutputUpdate 310
Contents 310
See Also 311
ParallelismConfiguration 312
Contents 312
See Also 313
ParallelismConfigurationDescription 314
Contents 314
See Also 315
ParallelismConfigurationUpdate 316
Contents 316
See Also 317
PropertyGroup 318
Contents 318
See Also 318
RecordColumn 319
Contents 319
See Also 319
RecordFormat 321
Contents 321
See Also 321
ReferenceDataSource 322
Contents 322
See Also 322
ReferenceDataSourceDescription 324
Contents 324
See Also 325
ReferenceDataSourceUpdate 326
Contents 326
See Also 327
RunConfiguration 328
Contents 328
See Also 328
RunConfigurationDescription 329
Contents 329
See Also 329

RunConfigurationUpdate 330
Contents 330
See Also 330
S3ApplicationCodeLocationDescription 331
Contents 331
See Also 331
S3Configuration 333
Contents 333
See Also 333
S3ContentBaseLocation 334
Contents 334
See Also 334
S3ContentBaseLocationDescription 335
Contents 335
See Also 335
S3ContentBaseLocationUpdate 336
Contents 336
See Also 336
S3ContentLocation 337
Contents 337
See Also 337
S3ContentLocationUpdate 339
Contents 339
See Also 339
S3ReferenceDataSource 341
Contents 341
See Also 341
S3ReferenceDataSourceDescription 342
Contents 342
See Also 343
S3ReferenceDataSourceUpdate 344
Contents 344
See Also 344
SnapshotDetails 345
Contents 345
See Also 346

SourceSchema 347
Contents 347
See Also 347
SqlApplicationConfiguration 349
Contents 349
See Also 349
SqlApplicationConfigurationDescription 350
Contents 350
See Also 350
SqlApplicationConfigurationUpdate 352
Contents 352
See Also 352
SqlRunConfiguration 354
Contents 354
See Also 354
Tag 355
Contents 355
See Also 355
VpcConfiguration 356
Contents 356
See Also 356
VpcConfigurationDescription 357
Contents 357
See Also 358
VpcConfigurationUpdate 359
Contents 359
See Also 359
ZeppelinApplicationConfiguration 361
Contents 361
See Also 362
ZeppelinApplicationConfigurationDescription 363
Contents 363
See Also 364
ZeppelinApplicationConfigurationUpdate 365
Contents 365
See Also 365

ZeppelinMonitoringConfiguration 367
Contents 367
See Also 367
ZeppelinMonitoringConfigurationDescription 368
Contents 368
See Also 368
ZeppelinMonitoringConfigurationUpdate 369
Contents 369
See Also 369

Welcome

> **Note**
>
> Amazon Managed Service for Apache Flink was previously known as Amazon Kinesis Data Analytics for Apache Flink.

Amazon Managed Service for Apache Flink is a fully managed service that you can use to process and analyze streaming data using Java, Python, SQL, or Scala. The service enables you to quickly author and run Java, SQL, or Scala code against streaming sources to perform time series analytics, feed real-time dashboards, and create real-time metrics.

This document was last published on October 14, 2026.

Actions

The following actions are supported:

- AddApplicationCloudWatchLoggingOption
- AddApplicationInput
- AddApplicationInputProcessingConfiguration
- AddApplicationOutput
- AddApplicationReferenceDataSource
- AddApplicationVpcConfiguration
- CreateApplication
- CreateApplicationPresignedUrl
- CreateApplicationSnapshot
- DeleteApplication
- DeleteApplicationCloudWatchLoggingOption
- DeleteApplicationInputProcessingConfiguration
- DeleteApplicationOutput
- DeleteApplicationReferenceDataSource
- DeleteApplicationSnapshot
- DeleteApplicationVpcConfiguration
- DescribeApplication
- DescribeApplicationOperation
- DescribeApplicationSnapshot
- DescribeApplicationVersion
- DiscoverInputSchema
- ListApplicationOperations
- ListApplications
- ListApplicationSnapshots
- ListApplicationVersions
- ListTagsForResource
- RollbackApplication

- StartApplication
- StopApplication
- TagResource
- UntagResource
- UpdateApplication
- UpdateApplicationMaintenanceConfiguration

AddApplicationCloudWatchLoggingOption

Adds an Amazon CloudWatch log stream to monitor application configuration errors.

Request Syntax

```
{
   "ApplicationName": "string",
   "CloudWatchLoggingOption": {
      "LogStreamARN": "string"
   },
   "ConditionalToken": "string",
   "CurrentApplicationVersionId": number
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The Kinesis Data Analytics application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CloudWatchLoggingOption

Provides the Amazon CloudWatch log stream Amazon Resource Name (ARN).

Type: CloudWatchLoggingOption object

Required: Yes

ConditionalToken

A value you use to implement strong concurrency for application updates. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You get the application's

current `ConditionalToken` using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CurrentApplicationVersionId

The version ID of the SQL-based Kinesis Data Analytics application. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`.You can retrieve the application version ID using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "CloudWatchLoggingOptionDescriptions": [
      {
         "CloudWatchLoggingOptionId": "string",
         "LogStreamARN": "string",
         "RoleARN": "string"
      }
   ],
   "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application's ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The new version ID of the SQL-based Kinesis Data Analytics application. Kinesis Data Analytics updates the `ApplicationVersionId` each time you change the CloudWatch logging options.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

CloudWatchLoggingOptionDescriptions

The descriptions of the current CloudWatch logging options for the SQL-based Kinesis Data Analytics application.

Type: Array of CloudWatchLoggingOptionDescription objects

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

AddApplicationInput

Adds a streaming source to your SQL-based Kinesis Data Analytics application.

You can add a streaming source when you create an application, or you can use this operation to add a streaming source after you create an application. For more information, see CreateApplication.

Any configuration update, including adding a streaming source using this operation, results in a new version of the application. You can use the DescribeApplication operation to find the current application version.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "Input": {
      "InputParallelism": {
         "Count": number
      },
      "InputProcessingConfiguration": {
         "InputLambdaProcessor": {
            "ResourceARN": "string"
         }
      },
      "InputSchema": {
         "RecordColumns": [
            {
               "Mapping": "string",
               "Name": "string",
               "SqlType": "string"
            }
         ],
         "RecordEncoding": "string",
         "RecordFormat": {
            "MappingParameters": {
               "CSVMappingParameters": {
                  "RecordColumnDelimiter": "string",
                  "RecordRowDelimiter": "string"
               },
               "JSONMappingParameters": {
```

```
                    "RecordRowPath": "string"
                }
            },
            "RecordFormatType": "string"
        }
    },
    "KinesisFirehoseInput": {
        "ResourceARN": "string"
    },
    "KinesisStreamsInput": {
        "ResourceARN": "string"
    },
    "NamePrefix": "string"
  }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of your existing application to which you want to add the streaming source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The current version of your application. You must provide the `ApplicationVersionID` or the `ConditionalToken`.You can use the DescribeApplication operation to find the current application version.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

Input

The Input to add.

Type: Input object

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "InputDescriptions": [
      {
         "InAppStreamNames": [ "string" ],
         "InputId": "string",
         "InputParallelism": {
            "Count": number
         },
         "InputProcessingConfigurationDescription": {
            "InputLambdaProcessorDescription": {
               "ResourceARN": "string",
               "RoleARN": "string"
            }
         },
         "InputSchema": {
            "RecordColumns": [
               {
                  "Mapping": "string",
                  "Name": "string",
                  "SqlType": "string"
               }
            ],
            "RecordEncoding": "string",
            "RecordFormat": {
               "MappingParameters": {
                  "CSVMappingParameters": {
                     "RecordColumnDelimiter": "string",
                     "RecordRowDelimiter": "string"
                  },
                  "JSONMappingParameters": {
                     "RecordRowPath": "string"
```

```
                    }
                },
                "RecordFormatType": "string"
            }
        },
        "InputStartingPositionConfiguration": {
            "InputStartingPosition": "string"
        },
        "KinesisFirehoseInputDescription": {
            "ResourceARN": "string",
            "RoleARN": "string"
        },
        "KinesisStreamsInputDescription": {
            "ResourceARN": "string",
            "RoleARN": "string"
        },
        "NamePrefix": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The Amazon Resource Name (ARN) of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

Provides the current application version.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

InputDescriptions

Describes the application input configuration.

Type: Array of InputDescription objects

Errors

CodeValidationException

The user-provided application code (query) is not valid. This can be a simple syntax error.

HTTP Status Code: 400

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

AddApplicationInputProcessingConfiguration

Adds an InputProcessingConfiguration to a SQL-based Kinesis Data Analytics application. An input processor pre-processes records on the input stream before the application's SQL code executes. Currently, the only input processor available is Amazon Lambda.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "InputId": "string",
   "InputProcessingConfiguration": {
      "InputLambdaProcessor": {
         "ResourceARN": "string"
      }
   }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application to which you want to add the input processing configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The version of the application to which you want to add the input processing configuration. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

InputId

The ID of the input configuration to add the input processing configuration to. You can get a list of the input IDs for an application using the DescribeApplication operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

InputProcessingConfiguration

The InputProcessingConfiguration to add to the application.

Type: InputProcessingConfiguration object

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "InputId": "string",
   "InputProcessingConfigurationDescription": {
      "InputLambdaProcessorDescription": {
         "ResourceARN": "string",
         "RoleARN": "string"
      }
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The Amazon Resource Name (ARN) of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

Provides the current application version.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

InputId

The input ID that is associated with the application input. This is the ID that Kinesis Data Analytics assigns to each input configuration that you add to your application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

InputProcessingConfigurationDescription

The description of the preprocessor that executes on records in this input before the application's code is run.

Type: InputProcessingConfigurationDescription object

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

AddApplicationOutput

Adds an external destination to your SQL-based Kinesis Data Analytics application.

If you want Kinesis Data Analytics to deliver data from an in-application stream within your application to an external destination (such as an Kinesis data stream, a Kinesis Data Firehose delivery stream, or an Amazon Lambda function), you add the relevant configuration to your application using this operation. You can configure one or more outputs for your application. Each output configuration maps an in-application stream and an external destination.

You can use one of the output configurations to deliver data from your in-application error stream to an external destination so that you can analyze the errors.

Any configuration update, including adding a streaming source using this operation, results in a new version of the application. You can use the DescribeApplication operation to find the current application version.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "Output": {
      "DestinationSchema": {
         "RecordFormatType": "string"
      },
      "KinesisFirehoseOutput": {
         "ResourceARN": "string"
      },
      "KinesisStreamsOutput": {
         "ResourceARN": "string"
      },
      "LambdaOutput": {
         "ResourceARN": "string"
      },
      "Name": "string"
   }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application to which you want to add the output configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The version of the application to which you want to add the output configuration. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

Output

An array of objects, each describing one output configuration. In the output configuration, you specify the name of an in-application stream, a destination (that is, a Kinesis data stream, a Kinesis Data Firehose delivery stream, or an Amazon Lambda function), and record the formation to use when writing to the destination.

Type: Output object

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
```

```
    "ApplicationVersionId": number,
    "OutputDescriptions": [
       {
          "DestinationSchema": {
             "RecordFormatType": "string"
          },
          "KinesisFirehoseOutputDescription": {
             "ResourceARN": "string",
             "RoleARN": "string"
          },
          "KinesisStreamsOutputDescription": {
             "ResourceARN": "string",
             "RoleARN": "string"
          },
          "LambdaOutputDescription": {
             "ResourceARN": "string",
             "RoleARN": "string"
          },
          "Name": "string",
          "OutputId": "string"
       }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The updated application version ID. Kinesis Data Analytics increments this ID when the application is updated.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

OutputDescriptions

Describes the application output configuration. For more information, see Configuring Application Output.

Type: Array of OutputDescription objects

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

AddApplicationReferenceDataSource

Adds a reference data source to an existing SQL-based Kinesis Data Analytics application.

Kinesis Data Analytics reads reference data (that is, an Amazon S3 object) and creates an in-application table within your application. In the request, you provide the source (S3 bucket name and object key name), name of the in-application table to create, and the necessary mapping information that describes how data in an Amazon S3 object maps to columns in the resulting in-application table.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "ReferenceDataSource": {
      "ReferenceSchema": {
         "RecordColumns": [
            {
               "Mapping": "string",
               "Name": "string",
               "SqlType": "string"
            }
         ],
         "RecordEncoding": "string",
         "RecordFormat": {
            "MappingParameters": {
               "CSVMappingParameters": {
                  "RecordColumnDelimiter": "string",
                  "RecordRowDelimiter": "string"
               },
               "JSONMappingParameters": {
                  "RecordRowPath": "string"
               }
            },
            "RecordFormatType": "string"
         }
      },
      "S3ReferenceDataSource": {
         "BucketARN": "string",
         "FileKey": "string"
      },
```

```
        "TableName": "string"
    }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The version of the application for which you are adding the reference data source. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

ReferenceDataSource

The reference data source can be an object in your Amazon S3 bucket. Kinesis Data Analytics reads the object and copies the data into the in-application table that is created. You provide an S3 bucket, object key name, and the resulting in-application table that is created.

Type: ReferenceDataSource object

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "ReferenceDataSourceDescriptions": [
      {
         "ReferenceId": "string",
         "ReferenceSchema": {
            "RecordColumns": [
               {
                  "Mapping": "string",
                  "Name": "string",
                  "SqlType": "string"
               }
            ],
            "RecordEncoding": "string",
            "RecordFormat": {
               "MappingParameters": {
                  "CSVMappingParameters": {
                     "RecordColumnDelimiter": "string",
                     "RecordRowDelimiter": "string"
                  },
                  "JSONMappingParameters": {
                     "RecordRowPath": "string"
                  }
               },
               "RecordFormatType": "string"
            }
         },
         "S3ReferenceDataSourceDescription": {
            "BucketARN": "string",
            "FileKey": "string",
            "ReferenceRoleARN": "string"
         },
         "TableName": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The updated application version ID. Kinesis Data Analytics increments this ID when the application is updated.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

ReferenceDataSourceDescriptions

Describes reference data sources configured for the application.

Type: Array of ReferenceDataSourceDescription objects

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

AddApplicationVpcConfiguration

Adds a Virtual Private Cloud (VPC) configuration to the application. Applications can use VPCs to store and access resources securely.

Note the following about VPC configurations for Managed Service for Apache Flink applications:

- VPC configurations are not supported for SQL applications.
- When a VPC is added to a Managed Service for Apache Flink application, the application can no longer be accessed from the Internet directly. To enable Internet access to the application, add an Internet gateway to your VPC.

Request Syntax

```
{
   "ApplicationName": "string",
   "ConditionalToken": "string",
   "CurrentApplicationVersionId": number,
   "VpcConfiguration": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
   }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ConditionalToken

A value you use to implement strong concurrency for application updates. You must provide the `ApplicationVersionID` or the `ConditionalToken`. You get the application's current `ConditionalToken` using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CurrentApplicationVersionId

The version of the application to which you want to add the VPC configuration. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

VpcConfiguration

Description of the VPC to add to the application.

Type: VpcConfiguration object

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
```

```
    "OperationId": "string",
    "VpcConfigurationDescription": {
       "SecurityGroupIds": [ "string" ],
       "SubnetIds": [ "string" ],
       "VpcConfigurationId": "string",
       "VpcId": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The ARN of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

Provides the current application version. Managed Service for Apache Flink updates the ApplicationVersionId each time you update the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

VpcConfigurationDescription

The parameters of the new VPC configuration.

Type: VpcConfigurationDescription object

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

CreateApplication

Creates a Managed Service for Apache Flink application. For information about creating a Managed Service for Apache Flink application, see Creating an Application.

Request Syntax

```
{
   "ApplicationConfiguration": {
      "ApplicationCodeConfiguration": {
         "CodeContent": {
            "S3ContentLocation": {
               "BucketARN": "string",
               "FileKey": "string",
               "ObjectVersion": "string"
            },
            "TextContent": "string",
            "ZipFileContent": blob
         },
         "CodeContentType": "string"
      },
      "ApplicationEncryptionConfiguration": {
         "KeyId": "string",
         "KeyType": "string"
      },
      "ApplicationSnapshotConfiguration": {
         "SnapshotsEnabled": boolean
      },
      "ApplicationSystemRollbackConfiguration": {
         "RollbackEnabled": boolean
      },
      "EnvironmentProperties": {
         "PropertyGroups": [
            {
               "PropertyGroupId": "string",
               "PropertyMap": {
                  "string" : "string"
               }
            }
         ]
      },
      "FlinkApplicationConfiguration": {
         "CheckpointConfiguration": {
```

```
            "CheckpointingEnabled": boolean,
            "CheckpointInterval": number,
            "ConfigurationType": "string",
            "MinPauseBetweenCheckpoints": number
         },
         "MonitoringConfiguration": {
            "ConfigurationType": "string",
            "LogLevel": "string",
            "MetricsLevel": "string"
         },
         "ParallelismConfiguration": {
            "AutoScalingEnabled": boolean,
            "ConfigurationType": "string",
            "Parallelism": number,
            "ParallelismPerKPU": number
         }
      },
      "SqlApplicationConfiguration": {
         "Inputs": [
            {
               "InputParallelism": {
                  "Count": number
               },
               "InputProcessingConfiguration": {
                  "InputLambdaProcessor": {
                     "ResourceARN": "string"
                  }
               },
               "InputSchema": {
                  "RecordColumns": [
                     {
                        "Mapping": "string",
                        "Name": "string",
                        "SqlType": "string"
                     }
                  ],
                  "RecordEncoding": "string",
                  "RecordFormat": {
                     "MappingParameters": {
                        "CSVMappingParameters": {
                           "RecordColumnDelimiter": "string",
                           "RecordRowDelimiter": "string"
                        },
                        "JSONMappingParameters": {
```

```
                        "RecordRowPath": "string"
                    }
                },
                "RecordFormatType": "string"
            }
        },
        "KinesisFirehoseInput": {
            "ResourceARN": "string"
        },
        "KinesisStreamsInput": {
            "ResourceARN": "string"
        },
        "NamePrefix": "string"
    }
],
"Outputs": [
    {
        "DestinationSchema": {
            "RecordFormatType": "string"
        },
        "KinesisFirehoseOutput": {
            "ResourceARN": "string"
        },
        "KinesisStreamsOutput": {
            "ResourceARN": "string"
        },
        "LambdaOutput": {
            "ResourceARN": "string"
        },
        "Name": "string"
    }
],
"ReferenceDataSources": [
    {
        "ReferenceSchema": {
            "RecordColumns": [
                {
                    "Mapping": "string",
                    "Name": "string",
                    "SqlType": "string"
                }
            ],
            "RecordEncoding": "string",
            "RecordFormat": {
```

```
                    "MappingParameters": {
                       "CSVMappingParameters": {
                          "RecordColumnDelimiter": "string",
                          "RecordRowDelimiter": "string"
                       },
                       "JSONMappingParameters": {
                          "RecordRowPath": "string"
                       }
                    },
                    "RecordFormatType": "string"
                 }
              },
              "S3ReferenceDataSource": {
                 "BucketARN": "string",
                 "FileKey": "string"
              },
              "TableName": "string"
           }
        ]
     },
     "VpcConfigurations": [
        {
           "SecurityGroupIds": [ "string" ],
           "SubnetIds": [ "string" ]
        }
     ],
     "ZeppelinApplicationConfiguration": {
        "CatalogConfiguration": {
           "GlueDataCatalogConfiguration": {
              "DatabaseARN": "string"
           }
        },
        "CustomArtifactsConfiguration": [
           {
              "ArtifactType": "string",
              "MavenReference": {
                 "ArtifactId": "string",
                 "GroupId": "string",
                 "Version": "string"
              },
              "S3ContentLocation": {
                 "BucketARN": "string",
                 "FileKey": "string",
                 "ObjectVersion": "string"
```

```
                }
            }
        ],
        "DeployAsApplicationConfiguration": {
            "S3ContentLocation": {
                "BasePath": "string",
                "BucketARN": "string"
            }
        },
        "MonitoringConfiguration": {
            "LogLevel": "string"
        }
    }
},
"ApplicationDescription": "string",
"ApplicationMode": "string",
"ApplicationName": "string",
"CloudWatchLoggingOptions": [
    {
        "LogStreamARN": "string"
    }
],
"RuntimeEnvironment": "string",
"ServiceExecutionRole": "string",
"Tags": [
    {
        "Key": "string",
        "Value": "string"
    }
]
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationConfiguration

Use this parameter to configure the application.

Type: ApplicationConfiguration object

Required: No

ApplicationDescription

A summary description of the application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ApplicationMode

Use the `STREAMING` mode to create a Managed Service for Apache Flink application. To create a Managed Service for Apache Flink Studio notebook, use the `INTERACTIVE` mode.

Type: String

Valid Values: `STREAMING | INTERACTIVE`

Required: No

ApplicationName

The name of your application (for example, `sample-app`).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CloudWatchLoggingOptions

Use this parameter to configure an Amazon CloudWatch log stream to monitor application configuration errors.

Type: Array of CloudWatchLoggingOption objects

Required: No

RuntimeEnvironment

The runtime environment for the application.

Type: String

Valid Values: `SQL-1_0 | FLINK-1_6 | FLINK-1_8 | ZEPPELIN-FLINK-1_0 | FLINK-1_11 | FLINK-1_13 | ZEPPELIN-FLINK-2_0 | FLINK-1_15 | ZEPPELIN-FLINK-3_0 | FLINK-1_18 | FLINK-1_19 | FLINK-1_20`

Required: Yes

ServiceExecutionRole

The IAM role used by the application to access Kinesis data streams, Kinesis Data Firehose delivery streams, Amazon S3 objects, and other external resources.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

Tags

A list of one or more tags to assign to the application. A tag is a key-value pair that identifies an application. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50. For more information, see Using Tagging.

Type: Array of Tag objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Required: No

Response Syntax

```
{
   "ApplicationDetail": {
      "ApplicationARN": "string",
      "ApplicationConfigurationDescription": {
         "ApplicationCodeConfigurationDescription": {
            "CodeContentDescription": {
               "CodeMD5": "string",
               "CodeSize": number,
               "S3ApplicationCodeLocationDescription": {
                  "BucketARN": "string",
```

```
                "FileKey": "string",
                "ObjectVersion": "string"
            },
            "TextContent": "string"
        },
        "CodeContentType": "string"
    },
    "ApplicationEncryptionConfigurationDescription": {
        "KeyId": "string",
        "KeyType": "string"
    },
    "ApplicationSnapshotConfigurationDescription": {
        "SnapshotsEnabled": boolean
    },
    "ApplicationSystemRollbackConfigurationDescription": {
        "RollbackEnabled": boolean
    },
    "EnvironmentPropertyDescriptions": {
        "PropertyGroupDescriptions": [
            {
                "PropertyGroupId": "string",
                "PropertyMap": {
                    "string" : "string"
                }
            }
        ]
    },
    "FlinkApplicationConfigurationDescription": {
        "CheckpointConfigurationDescription": {
            "CheckpointingEnabled": boolean,
            "CheckpointInterval": number,
            "ConfigurationType": "string",
            "MinPauseBetweenCheckpoints": number
        },
        "JobPlanDescription": "string",
        "MonitoringConfigurationDescription": {
            "ConfigurationType": "string",
            "LogLevel": "string",
            "MetricsLevel": "string"
        },
        "ParallelismConfigurationDescription": {
            "AutoScalingEnabled": boolean,
            "ConfigurationType": "string",
            "CurrentParallelism": number,
```

```
                "Parallelism": number,
                "ParallelismPerKPU": number
            }
        },
        "RunConfigurationDescription": {
            "ApplicationRestoreConfigurationDescription": {
                "ApplicationRestoreType": "string",
                "SnapshotName": "string"
            },
            "FlinkRunConfigurationDescription": {
                "AllowNonRestoredState": boolean
            }
        },
        "SqlApplicationConfigurationDescription": {
            "InputDescriptions": [
                {
                    "InAppStreamNames": [ "string" ],
                    "InputId": "string",
                    "InputParallelism": {
                        "Count": number
                    },
                    "InputProcessingConfigurationDescription": {
                        "InputLambdaProcessorDescription": {
                            "ResourceARN": "string",
                            "RoleARN": "string"
                        }
                    },
                    "InputSchema": {
                        "RecordColumns": [
                            {
                                "Mapping": "string",
                                "Name": "string",
                                "SqlType": "string"
                            }
                        ],
                        "RecordEncoding": "string",
                        "RecordFormat": {
                            "MappingParameters": {
                                "CSVMappingParameters": {
                                    "RecordColumnDelimiter": "string",
                                    "RecordRowDelimiter": "string"
                                },
                                "JSONMappingParameters": {
                                    "RecordRowPath": "string"
```

```
                        }
                    },
                    "RecordFormatType": "string"
                }
            },
            "InputStartingPositionConfiguration": {
                "InputStartingPosition": "string"
            },
            "KinesisFirehoseInputDescription": {
                "ResourceARN": "string",
                "RoleARN": "string"
            },
            "KinesisStreamsInputDescription": {
                "ResourceARN": "string",
                "RoleARN": "string"
            },
            "NamePrefix": "string"
        }
    ],
    "OutputDescriptions": [
        {
            "DestinationSchema": {
                "RecordFormatType": "string"
            },
            "KinesisFirehoseOutputDescription": {
                "ResourceARN": "string",
                "RoleARN": "string"
            },
            "KinesisStreamsOutputDescription": {
                "ResourceARN": "string",
                "RoleARN": "string"
            },
            "LambdaOutputDescription": {
                "ResourceARN": "string",
                "RoleARN": "string"
            },
            "Name": "string",
            "OutputId": "string"
        }
    ],
    "ReferenceDataSourceDescriptions": [
        {
            "ReferenceId": "string",
            "ReferenceSchema": {
```

```
                "RecordColumns": [
                   {
                      "Mapping": "string",
                      "Name": "string",
                      "SqlType": "string"
                   }
                ],
                "RecordEncoding": "string",
                "RecordFormat": {
                   "MappingParameters": {
                      "CSVMappingParameters": {
                         "RecordColumnDelimiter": "string",
                         "RecordRowDelimiter": "string"
                      },
                      "JSONMappingParameters": {
                         "RecordRowPath": "string"
                      }
                   },
                   "RecordFormatType": "string"
                }
             },
             "S3ReferenceDataSourceDescription": {
                "BucketARN": "string",
                "FileKey": "string",
                "ReferenceRoleARN": "string"
             },
             "TableName": "string"
          }
       ]
    },
    "VpcConfigurationDescriptions": [
       {
          "SecurityGroupIds": [ "string" ],
          "SubnetIds": [ "string" ],
          "VpcConfigurationId": "string",
          "VpcId": "string"
       }
    ],
    "ZeppelinApplicationConfigurationDescription": {
       "CatalogConfigurationDescription": {
          "GlueDataCatalogConfigurationDescription": {
             "DatabaseARN": "string"
          }
       },
```

```
            "CustomArtifactsConfigurationDescription": [
               {
                  "ArtifactType": "string",
                  "MavenReferenceDescription": {
                     "ArtifactId": "string",
                     "GroupId": "string",
                     "Version": "string"
                  },
                  "S3ContentLocationDescription": {
                     "BucketARN": "string",
                     "FileKey": "string",
                     "ObjectVersion": "string"
                  }
               }
            ],
            "DeployAsApplicationConfigurationDescription": {
               "S3ContentLocationDescription": {
                  "BasePath": "string",
                  "BucketARN": "string"
               }
            },
            "MonitoringConfigurationDescription": {
               "LogLevel": "string"
            }
         }
      },
      "ApplicationDescription": "string",
      "ApplicationMaintenanceConfigurationDescription": {
         "ApplicationMaintenanceWindowEndTime": "string",
         "ApplicationMaintenanceWindowStartTime": "string"
      },
      "ApplicationMode": "string",
      "ApplicationName": "string",
      "ApplicationStatus": "string",
      "ApplicationVersionCreateTimestamp": number,
      "ApplicationVersionId": number,
      "ApplicationVersionRolledBackFrom": number,
      "ApplicationVersionRolledBackTo": number,
      "ApplicationVersionUpdatedFrom": number,
      "CloudWatchLoggingOptionDescriptions": [
         {
            "CloudWatchLoggingOptionId": "string",
            "LogStreamARN": "string",
            "RoleARN": "string"
```

```
            }
        ],
        "ConditionalToken": "string",
        "CreateTimestamp": number,
        "LastUpdateTimestamp": number,
        "RuntimeEnvironment": "string",
        "ServiceExecutionRole": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationDetail

In response to your `CreateApplication` request, Managed Service for Apache Flink returns a response with details of the application it created.

Type: ApplicationDetail object

Errors

CodeValidationException

The user-provided application code (query) is not valid. This can be a simple syntax error.

HTTP Status Code: 400

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

LimitExceededException

The number of allowed resources has been exceeded.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

TooManyTagsException

Application created with too many tags, or too many tags added to an application. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

CreateApplicationPresignedUrl

Creates and returns a URL that you can use to connect to an application's extension.

The IAM role or user used to call this API defines the permissions to access the extension. After the presigned URL is created, no additional permission is required to access this URL. IAM authorization policies for this API are also enforced for every HTTP request that attempts to connect to the extension.

You control the amount of time that the URL will be valid using the `SessionExpirationDurationInSeconds` parameter. If you do not provide this parameter, the returned URL is valid for twelve hours.

> **Note**
>
> The URL that you get from a call to CreateApplicationPresignedUrl must be used within 3 minutes to be valid. If you first try to use the URL after the 3-minute limit expires, the service returns an HTTP 403 Forbidden error.

Request Syntax

```
{
   "ApplicationName": "string",
   "SessionExpirationDurationInSeconds": number,
   "UrlType": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SessionExpirationDurationInSeconds

The duration in seconds for which the returned URL will be valid.

Type: Long

Valid Range: Minimum value of 1800. Maximum value of 43200.

Required: No

UrlType

The type of the extension for which to create and return a URL. Currently, the only valid extension URL type is `FLINK_DASHBOARD_URL`.

Type: String

Valid Values: `FLINK_DASHBOARD_URL | ZEPPELIN_UI_URL`

Required: Yes

Response Syntax

```
{
   "AuthorizedUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuthorizedUrl

The URL of the extension.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

CreateApplicationSnapshot

Creates a snapshot of the application's state data.

Request Syntax

```
{
   "ApplicationName": "string",
   "SnapshotName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SnapshotName

An identifier for the application snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

LimitExceededException

The number of allowed resources has been exceeded.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplication

Deletes the specified application. Managed Service for Apache Flink halts application execution and deletes the application.

Request Syntax

```
{
   "ApplicationName": "string",
   "CreateTimestamp": number
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CreateTimestamp

Use the `DescribeApplication` operation to get this value.

Type: Timestamp

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationCloudWatchLoggingOption

Deletes an Amazon CloudWatch log stream from an SQL-based Kinesis Data Analytics application.

Request Syntax

```
{
   "ApplicationName": "string",
   "CloudWatchLoggingOptionId": "string",
   "ConditionalToken": "string",
   "CurrentApplicationVersionId": number
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CloudWatchLoggingOptionId

The `CloudWatchLoggingOptionId` of the Amazon CloudWatch logging option to delete. You can get the `CloudWatchLoggingOptionId` by using the DescribeApplication operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ConditionalToken

A value you use to implement strong concurrency for application updates. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You get the application's current `ConditionalToken` using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CurrentApplicationVersionId

The version ID of the application. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You can retrieve the application version ID using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "CloudWatchLoggingOptionDescriptions": [
      {
         "CloudWatchLoggingOptionId": "string",
         "LogStreamARN": "string",
         "RoleARN": "string"
      }
   ],
   "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The version ID of the application. Kinesis Data Analytics updates the `ApplicationVersionId` each time you change the CloudWatch logging options.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

CloudWatchLoggingOptionDescriptions

The descriptions of the remaining CloudWatch logging options for the application.

Type: Array of CloudWatchLoggingOptionDescription objects

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationInputProcessingConfiguration

Deletes an InputProcessingConfiguration from an input.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "InputId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The application version. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

InputId

The ID of the input configuration from which to delete the input processing configuration. You can get a list of the input IDs for an application by using the DescribeApplication operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The Amazon Resource Name (ARN) of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The current application version ID.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationOutput

Deletes the output destination configuration from your SQL-based Kinesis Data Analytics application's configuration. Kinesis Data Analytics will no longer write data from the corresponding in-application stream to the external output destination.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "OutputId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The application name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The application version. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

OutputId

The ID of the configuration to delete. Each output configuration that is added to the application (either when the application is created or later) using the AddApplicationOutput operation has a unique ID. You need to provide the ID to uniquely identify the output configuration that you want to delete from the application configuration. You can use the DescribeApplication operation to get the specific `OutputId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The current application version ID.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationReferenceDataSource

Deletes a reference data source configuration from the specified SQL-based Kinesis Data Analytics application's configuration.

If the application is running, Kinesis Data Analytics immediately removes the in-application table that you created using the AddApplicationReferenceDataSource operation.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number,
   "ReferenceId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The current application version. You can use the DescribeApplication operation to get the current application version. If the version specified is not the current version, the `ConcurrentModificationException` is returned.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

ReferenceId

The ID of the reference data source. When you add a reference data source to your application using the AddApplicationReferenceDataSource, Kinesis Data Analytics assigns an ID. You can use the DescribeApplication operation to get the reference ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The application Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The updated version ID of the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationSnapshot

Deletes a snapshot of application state.

Request Syntax

```
{
   "ApplicationName": "string",
   "SnapshotCreationTimestamp": number,
   "SnapshotName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SnapshotCreationTimestamp

The creation timestamp of the application snapshot to delete. You can retrieve this value using DescribeApplicationSnapshot or ListApplicationSnapshots.

Type: Timestamp

Required: Yes

SnapshotName

The identifier for the snapshot delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DeleteApplicationVpcConfiguration

Removes a VPC configuration from a Managed Service for Apache Flink application.

Request Syntax

```
{
   "ApplicationName": "string",
   "ConditionalToken": "string",
   "CurrentApplicationVersionId": number,
   "VpcConfigurationId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ConditionalToken

A value you use to implement strong concurrency for application updates. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You get the application's current `ConditionalToken` using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CurrentApplicationVersionId

The current application version ID. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You can retrieve the application version ID using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

VpcConfigurationId

The ID of the VPC configuration to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationVersionId": number,
   "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The ARN of the Managed Service for Apache Flink application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationVersionId

The updated version ID of the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DescribeApplication

Returns information about a specific Managed Service for Apache Flink application.

If you want to retrieve a list of all applications in your account, use the ListApplications operation.

Request Syntax

```
{
   "ApplicationName": "string",
   "IncludeAdditionalDetails": boolean
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

IncludeAdditionalDetails

Displays verbose information about a Managed Service for Apache Flink application, including the application's job plan.

Type: Boolean

Required: No

Response Syntax

```
{
   "ApplicationDetail": {
      "ApplicationARN": "string",
```

```
        "ApplicationConfigurationDescription": {
           "ApplicationCodeConfigurationDescription": {
              "CodeContentDescription": {
                 "CodeMD5": "string",
                 "CodeSize": number,
                 "S3ApplicationCodeLocationDescription": {
                    "BucketARN": "string",
                    "FileKey": "string",
                    "ObjectVersion": "string"
                 },
                 "TextContent": "string"
              },
              "CodeContentType": "string"
           },
           "ApplicationEncryptionConfigurationDescription": {
              "KeyId": "string",
              "KeyType": "string"
           },
           "ApplicationSnapshotConfigurationDescription": {
              "SnapshotsEnabled": boolean
           },
           "ApplicationSystemRollbackConfigurationDescription": {
              "RollbackEnabled": boolean
           },
           "EnvironmentPropertyDescriptions": {
              "PropertyGroupDescriptions": [
                 {
                    "PropertyGroupId": "string",
                    "PropertyMap": {
                       "string" : "string"
                    }
                 }
              ]
           },
           "FlinkApplicationConfigurationDescription": {
              "CheckpointConfigurationDescription": {
                 "CheckpointingEnabled": boolean,
                 "CheckpointInterval": number,
                 "ConfigurationType": "string",
                 "MinPauseBetweenCheckpoints": number
              },
              "JobPlanDescription": "string",
              "MonitoringConfigurationDescription": {
                 "ConfigurationType": "string",
```

```
                "LogLevel": "string",
                "MetricsLevel": "string"
            },
            "ParallelismConfigurationDescription": {
                "AutoScalingEnabled": boolean,
                "ConfigurationType": "string",
                "CurrentParallelism": number,
                "Parallelism": number,
                "ParallelismPerKPU": number
            }
        },
        "RunConfigurationDescription": {
            "ApplicationRestoreConfigurationDescription": {
                "ApplicationRestoreType": "string",
                "SnapshotName": "string"
            },
            "FlinkRunConfigurationDescription": {
                "AllowNonRestoredState": boolean
            }
        },
        "SqlApplicationConfigurationDescription": {
            "InputDescriptions": [
                {
                    "InAppStreamNames": [ "string" ],
                    "InputId": "string",
                    "InputParallelism": {
                        "Count": number
                    },
                    "InputProcessingConfigurationDescription": {
                        "InputLambdaProcessorDescription": {
                            "ResourceARN": "string",
                            "RoleARN": "string"
                        }
                    },
                    "InputSchema": {
                        "RecordColumns": [
                            {
                                "Mapping": "string",
                                "Name": "string",
                                "SqlType": "string"
                            }
                        ],
                        "RecordEncoding": "string",
                        "RecordFormat": {
```

```
                    "MappingParameters": {
                       "CSVMappingParameters": {
                          "RecordColumnDelimiter": "string",
                          "RecordRowDelimiter": "string"
                       },
                       "JSONMappingParameters": {
                          "RecordRowPath": "string"
                       }
                    },
                    "RecordFormatType": "string"
                 }
              },
              "InputStartingPositionConfiguration": {
                 "InputStartingPosition": "string"
              },
              "KinesisFirehoseInputDescription": {
                 "ResourceARN": "string",
                 "RoleARN": "string"
              },
              "KinesisStreamsInputDescription": {
                 "ResourceARN": "string",
                 "RoleARN": "string"
              },
              "NamePrefix": "string"
           }
        ],
        "OutputDescriptions": [
           {
              "DestinationSchema": {
                 "RecordFormatType": "string"
              },
              "KinesisFirehoseOutputDescription": {
                 "ResourceARN": "string",
                 "RoleARN": "string"
              },
              "KinesisStreamsOutputDescription": {
                 "ResourceARN": "string",
                 "RoleARN": "string"
              },
              "LambdaOutputDescription": {
                 "ResourceARN": "string",
                 "RoleARN": "string"
              },
              "Name": "string",
```

```
                "OutputId": "string"
            }
        ],
        "ReferenceDataSourceDescriptions": [
            {
                "ReferenceId": "string",
                "ReferenceSchema": {
                    "RecordColumns": [
                        {
                            "Mapping": "string",
                            "Name": "string",
                            "SqlType": "string"
                        }
                    ],
                    "RecordEncoding": "string",
                    "RecordFormat": {
                        "MappingParameters": {
                            "CSVMappingParameters": {
                                "RecordColumnDelimiter": "string",
                                "RecordRowDelimiter": "string"
                            },
                            "JSONMappingParameters": {
                                "RecordRowPath": "string"
                            }
                        },
                        "RecordFormatType": "string"
                    }
                },
                "S3ReferenceDataSourceDescription": {
                    "BucketARN": "string",
                    "FileKey": "string",
                    "ReferenceRoleARN": "string"
                },
                "TableName": "string"
            }
        ]
    },
    "VpcConfigurationDescriptions": [
        {
            "SecurityGroupIds": [ "string" ],
            "SubnetIds": [ "string" ],
            "VpcConfigurationId": "string",
            "VpcId": "string"
        }
```

```
            ],
            "ZeppelinApplicationConfigurationDescription": {
               "CatalogConfigurationDescription": {
                  "GlueDataCatalogConfigurationDescription": {
                     "DatabaseARN": "string"
                  }
               },
               "CustomArtifactsConfigurationDescription": [
                  {
                     "ArtifactType": "string",
                     "MavenReferenceDescription": {
                        "ArtifactId": "string",
                        "GroupId": "string",
                        "Version": "string"
                     },
                     "S3ContentLocationDescription": {
                        "BucketARN": "string",
                        "FileKey": "string",
                        "ObjectVersion": "string"
                     }
                  }
               ],
               "DeployAsApplicationConfigurationDescription": {
                  "S3ContentLocationDescription": {
                     "BasePath": "string",
                     "BucketARN": "string"
                  }
               },
               "MonitoringConfigurationDescription": {
                  "LogLevel": "string"
               }
            }
         },
         "ApplicationDescription": "string",
         "ApplicationMaintenanceConfigurationDescription": {
            "ApplicationMaintenanceWindowEndTime": "string",
            "ApplicationMaintenanceWindowStartTime": "string"
         },
         "ApplicationMode": "string",
         "ApplicationName": "string",
         "ApplicationStatus": "string",
         "ApplicationVersionCreateTimestamp": number,
         "ApplicationVersionId": number,
         "ApplicationVersionRolledBackFrom": number,
```

```
        "ApplicationVersionRolledBackTo": number,
        "ApplicationVersionUpdatedFrom": number,
        "CloudWatchLoggingOptionDescriptions": [
           {
              "CloudWatchLoggingOptionId": "string",
              "LogStreamARN": "string",
              "RoleARN": "string"
           }
        ],
        "ConditionalToken": "string",
        "CreateTimestamp": number,
        "LastUpdateTimestamp": number,
        "RuntimeEnvironment": "string",
        "ServiceExecutionRole": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationDetail

Provides a description of the application, such as the application's Amazon Resource Name (ARN), status, and latest version.

Type: ApplicationDetail object

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DescribeApplicationOperation

Provides a detailed description of a specified application operation. To see a list of all the operations of an application, invoke the ListApplicationOperations operation.

> **Note**
>
> This operation is supported only for Managed Service for Apache Flink.

Request Syntax

```
{
   "ApplicationName": "string",
   "OperationId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

OperationId

The operation ID of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{
   "ApplicationOperationInfoDetails": {
      "ApplicationVersionChangeDetails": {
         "ApplicationVersionUpdatedFrom": number,
         "ApplicationVersionUpdatedTo": number
      },
      "EndTime": number,
      "Operation": "string",
      "OperationFailureDetails": {
         "ErrorInfo": {
            "ErrorString": "string"
         },
         "RollbackOperationId": "string"
      },
      "OperationStatus": "string",
      "StartTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationOperationInfoDetails

A description of the application operation that provides information about the updates that were made to the application.

Type: ApplicationOperationInfoDetails object

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DescribeApplicationSnapshot

Returns information about a snapshot of application state data.

Request Syntax

```
{
   "ApplicationName": "string",
   "SnapshotName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SnapshotName

The identifier of an application snapshot. You can retrieve this value using ListApplicationSnapshots.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
```

```
    "SnapshotDetails": {
       "ApplicationEncryptionConfigurationDescription": {
          "KeyId": "string",
          "KeyType": "string"
       },
       "ApplicationVersionId": number,
       "RuntimeEnvironment": "string",
       "SnapshotCreationTimestamp": number,
       "SnapshotName": "string",
       "SnapshotStatus": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SnapshotDetails

An object containing information about the application snapshot.

Type: SnapshotDetails object

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DescribeApplicationVersion

Provides a detailed description of a specified version of the application. To see a list of all the versions of an application, invoke the ListApplicationVersions operation.

> **Note**
>
> This operation is supported only for Managed Service for Apache Flink.

Request Syntax

```
{
   "ApplicationName": "string",
   "ApplicationVersionId": number
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application for which you want to get the version description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ApplicationVersionId

The ID of the application version for which you want to get the description.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

Response Syntax

```
{
   "ApplicationVersionDetail": {
      "ApplicationARN": "string",
      "ApplicationConfigurationDescription": {
         "ApplicationCodeConfigurationDescription": {
            "CodeContentDescription": {
               "CodeMD5": "string",
               "CodeSize": number,
               "S3ApplicationCodeLocationDescription": {
                  "BucketARN": "string",
                  "FileKey": "string",
                  "ObjectVersion": "string"
               },
               "TextContent": "string"
            },
            "CodeContentType": "string"
         },
         "ApplicationEncryptionConfigurationDescription": {
            "KeyId": "string",
            "KeyType": "string"
         },
         "ApplicationSnapshotConfigurationDescription": {
            "SnapshotsEnabled": boolean
         },
         "ApplicationSystemRollbackConfigurationDescription": {
            "RollbackEnabled": boolean
         },
         "EnvironmentPropertyDescriptions": {
            "PropertyGroupDescriptions": [
               {
                  "PropertyGroupId": "string",
                  "PropertyMap": {
                     "string" : "string"
                  }
               }
            ]
         },
         "FlinkApplicationConfigurationDescription": {
            "CheckpointConfigurationDescription": {
               "CheckpointingEnabled": boolean,
               "CheckpointInterval": number,
```

```
                "ConfigurationType": "string",
                "MinPauseBetweenCheckpoints": number
            },
            "JobPlanDescription": "string",
            "MonitoringConfigurationDescription": {
                "ConfigurationType": "string",
                "LogLevel": "string",
                "MetricsLevel": "string"
            },
            "ParallelismConfigurationDescription": {
                "AutoScalingEnabled": boolean,
                "ConfigurationType": "string",
                "CurrentParallelism": number,
                "Parallelism": number,
                "ParallelismPerKPU": number
            }
        },
        "RunConfigurationDescription": {
            "ApplicationRestoreConfigurationDescription": {
                "ApplicationRestoreType": "string",
                "SnapshotName": "string"
            },
            "FlinkRunConfigurationDescription": {
                "AllowNonRestoredState": boolean
            }
        },
        "SqlApplicationConfigurationDescription": {
            "InputDescriptions": [
                {
                    "InAppStreamNames": [ "string" ],
                    "InputId": "string",
                    "InputParallelism": {
                        "Count": number
                    },
                    "InputProcessingConfigurationDescription": {
                        "InputLambdaProcessorDescription": {
                            "ResourceARN": "string",
                            "RoleARN": "string"
                        }
                    },
                    "InputSchema": {
                        "RecordColumns": [
                            {
                                "Mapping": "string",
```

```
                        "Name": "string",
                        "SqlType": "string"
                     }
                  ],
                  "RecordEncoding": "string",
                  "RecordFormat": {
                     "MappingParameters": {
                        "CSVMappingParameters": {
                           "RecordColumnDelimiter": "string",
                           "RecordRowDelimiter": "string"
                        },
                        "JSONMappingParameters": {
                           "RecordRowPath": "string"
                        }
                     },
                     "RecordFormatType": "string"
                  }
               },
               "InputStartingPositionConfiguration": {
                  "InputStartingPosition": "string"
               },
               "KinesisFirehoseInputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "KinesisStreamsInputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "NamePrefix": "string"
            }
         ],
         "OutputDescriptions": [
            {
               "DestinationSchema": {
                  "RecordFormatType": "string"
               },
               "KinesisFirehoseOutputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "KinesisStreamsOutputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
```

```
                },
                "LambdaOutputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "Name": "string",
                "OutputId": "string"
             }
          ],
          "ReferenceDataSourceDescriptions": [
             {
                "ReferenceId": "string",
                "ReferenceSchema": {
                   "RecordColumns": [
                      {
                         "Mapping": "string",
                         "Name": "string",
                         "SqlType": "string"
                      }
                   ],
                   "RecordEncoding": "string",
                   "RecordFormat": {
                      "MappingParameters": {
                         "CSVMappingParameters": {
                            "RecordColumnDelimiter": "string",
                            "RecordRowDelimiter": "string"
                         },
                         "JSONMappingParameters": {
                            "RecordRowPath": "string"
                         }
                      },
                      "RecordFormatType": "string"
                   }
                },
                "S3ReferenceDataSourceDescription": {
                   "BucketARN": "string",
                   "FileKey": "string",
                   "ReferenceRoleARN": "string"
                },
                "TableName": "string"
             }
          ]
       },
       "VpcConfigurationDescriptions": [
```

```
            {
               "SecurityGroupIds": [ "string" ],
               "SubnetIds": [ "string" ],
               "VpcConfigurationId": "string",
               "VpcId": "string"
            }
         ],
         "ZeppelinApplicationConfigurationDescription": {
            "CatalogConfigurationDescription": {
               "GlueDataCatalogConfigurationDescription": {
                  "DatabaseARN": "string"
               }
            },
            "CustomArtifactsConfigurationDescription": [
               {
                  "ArtifactType": "string",
                  "MavenReferenceDescription": {
                     "ArtifactId": "string",
                     "GroupId": "string",
                     "Version": "string"
                  },
                  "S3ContentLocationDescription": {
                     "BucketARN": "string",
                     "FileKey": "string",
                     "ObjectVersion": "string"
                  }
               }
            ],
            "DeployAsApplicationConfigurationDescription": {
               "S3ContentLocationDescription": {
                  "BasePath": "string",
                  "BucketARN": "string"
               }
            },
            "MonitoringConfigurationDescription": {
               "LogLevel": "string"
            }
         }
      },
      "ApplicationDescription": "string",
      "ApplicationMaintenanceConfigurationDescription": {
         "ApplicationMaintenanceWindowEndTime": "string",
         "ApplicationMaintenanceWindowStartTime": "string"
      },
```

```
        "ApplicationMode": "string",
        "ApplicationName": "string",
        "ApplicationStatus": "string",
        "ApplicationVersionCreateTimestamp": number,
        "ApplicationVersionId": number,
        "ApplicationVersionRolledBackFrom": number,
        "ApplicationVersionRolledBackTo": number,
        "ApplicationVersionUpdatedFrom": number,
        "CloudWatchLoggingOptionDescriptions": [
           {
              "CloudWatchLoggingOptionId": "string",
              "LogStreamARN": "string",
              "RoleARN": "string"
           }
        ],
        "ConditionalToken": "string",
        "CreateTimestamp": number,
        "LastUpdateTimestamp": number,
        "RuntimeEnvironment": "string",
        "ServiceExecutionRole": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationVersionDetail

Describes the application, including the application Amazon Resource Name (ARN), status, latest version, and input and output configurations.

Type: ApplicationDetail object

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

DiscoverInputSchema

Infers a schema for a SQL-based Kinesis Data Analytics application by evaluating sample records on the specified streaming source (Kinesis data stream or Kinesis Data Firehose delivery stream) or Amazon S3 object. In the response, the operation returns the inferred schema and also the sample records that the operation used to infer the schema.

You can use the inferred schema when configuring a streaming source for your application. When you create an application using the Kinesis Data Analytics console, the console uses this operation to infer a schema and show it in the console user interface.

Request Syntax

```
{
   "InputProcessingConfiguration": {
      "InputLambdaProcessor": {
         "ResourceARN": "string"
      }
   },
   "InputStartingPositionConfiguration": {
      "InputStartingPosition": "string"
   },
   "ResourceARN": "string",
   "S3Configuration": {
      "BucketARN": "string",
      "FileKey": "string"
   },
   "ServiceExecutionRole": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

InputProcessingConfiguration

The InputProcessingConfiguration to use to preprocess the records before discovering the schema of the records.

Type: InputProcessingConfiguration object

Required: No

InputStartingPositionConfiguration

The point at which you want Kinesis Data Analytics to start reading records from the specified streaming source for discovery purposes.

Type: InputStartingPositionConfiguration object

Required: No

ResourceARN

The Amazon Resource Name (ARN) of the streaming source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

S3Configuration

Specify this parameter to discover a schema from data in an Amazon S3 object.

Type: S3Configuration object

Required: No

ServiceExecutionRole

The ARN of the role that is used to access the streaming source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

Response Syntax

```
{
```

```
    "InputSchema": {
       "RecordColumns": [
          {
             "Mapping": "string",
             "Name": "string",
             "SqlType": "string"
          }
       ],
       "RecordEncoding": "string",
       "RecordFormat": {
          "MappingParameters": {
             "CSVMappingParameters": {
                "RecordColumnDelimiter": "string",
                "RecordRowDelimiter": "string"
             },
             "JSONMappingParameters": {
                "RecordRowPath": "string"
             }
          },
          "RecordFormatType": "string"
       }
    },
    "ParsedInputRecords": [
       [ "string" ]
    ],
    "ProcessedInputRecords": [ "string" ],
    "RawInputRecords": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InputSchema

The schema inferred from the streaming source. It identifies the format of the data in the streaming source and how each data element maps to corresponding columns in the in-application stream that you can create.

Type: SourceSchema object

ParsedInputRecords

An array of elements, where each element corresponds to a row in a stream record (a stream record can have more than one row).

Type: Array of arrays of strings

ProcessedInputRecords

The stream data that was modified by the processor specified in the `InputProcessingConfiguration` parameter.

Type: Array of strings

RawInputRecords

The raw stream data that was sampled to infer the schema.

Type: Array of strings

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceProvisionedThroughputExceededException

Discovery failed to get a record from the streaming source because of the Kinesis Streams `ProvisionedThroughputExceededException`. For more information, see GetRecords in the Amazon Kinesis Streams API Reference.

HTTP Status Code: 400

ServiceUnavailableException

The service cannot complete the request.

HTTP Status Code: 500

UnableToDetectSchemaException

The data format is not valid. Kinesis Data Analytics cannot detect the schema for the given streaming source.

ProcessedInputRecords

Stream data that was modified by the processor specified in the `InputProcessingConfiguration` parameter.

RawInputRecords

Raw stream data that was sampled to infer the schema.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

ListApplicationOperations

Lists all the operations performed for the specified application such as UpdateApplication, StartApplication etc. The response also includes a summary of the operation.

To get the complete description of a specific operation, invoke the DescribeApplicationOperation operation.

> **Note**
>
> This operation is supported only for Managed Service for Apache Flink.

Request Syntax

```
{
   "ApplicationName": "string",
   "Limit": number,
   "NextToken": "string",
   "Operation": "string",
   "OperationStatus": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Limit

The limit on the number of records to be returned in the response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

A pagination token that can be used in a subsequent request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Operation

The type of operation that is performed on an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

OperationStatus

The status of the operation.

Type: String

Valid Values: `IN_PROGRESS | CANCELLED | SUCCESSFUL | FAILED`

Required: No

Response Syntax

```
{
   "ApplicationOperationInfoList": [
      {
         "EndTime": number,
         "Operation": "string",
         "OperationId": "string",
         "OperationStatus": "string",
```

```
            "StartTime": number
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationOperationInfoList

A list of `ApplicationOperationInfo` objects that are associated with an application.

Type: Array of ApplicationOperationInfo objects

NextToken

A pagination token that can be used in a subsequent request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

ListApplications

Returns a list of Managed Service for Apache Flink applications in your account. For each application, the response includes the application name, Amazon Resource Name (ARN), and status.

If you want detailed information about a specific application, use DescribeApplication.

Request Syntax

```
{
   "Limit": number,
   "NextToken": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

Limit

The maximum number of applications to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

If a previous command returned a pagination token, pass it into this value to retrieve the next set of results. For more information about pagination, see Using the Amazon Command Line Interface's Pagination Options.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

Response Syntax

```
{
   "ApplicationSummaries": [
      {
         "ApplicationARN": "string",
         "ApplicationMode": "string",
         "ApplicationName": "string",
         "ApplicationStatus": "string",
         "ApplicationVersionId": number,
         "RuntimeEnvironment": "string"
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationSummaries

A list of `ApplicationSummary` objects.

Type: Array of ApplicationSummary objects

NextToken

The pagination token for the next set of results, or `null` if there are no additional results. Pass this token into a subsequent command to retrieve the next set of items For more information about pagination, see Using the Amazon Command Line Interface's Pagination Options.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Errors

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

ListApplicationSnapshots

Lists information about the current application snapshots.

Request Syntax

```
{
   "ApplicationName": "string",
   "Limit": number,
   "NextToken": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of an existing application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Limit

The maximum number of application snapshots to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

Use this parameter if you receive a `NextToken` response in a previous request that indicates that there is more output available. Set it to the value of the previous call's `NextToken` response to indicate where the output should continue from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "SnapshotSummaries": [
      {
         "ApplicationEncryptionConfigurationDescription": {
            "KeyId": "string",
            "KeyType": "string"
         },
         "ApplicationVersionId": number,
         "RuntimeEnvironment": "string",
         "SnapshotCreationTimestamp": number,
         "SnapshotName": "string",
         "SnapshotStatus": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next set of results, or `null` if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

SnapshotSummaries

A collection of objects containing information about the application snapshots.

Type: Array of SnapshotDetails objects

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

ListApplicationVersions

Lists all the versions for the specified application, including versions that were rolled back. The response also includes a summary of the configuration associated with each version.

To get the complete description of a specific application version, invoke the DescribeApplicationVersion operation.

> **Note**
>
> This operation is supported only for Managed Service for Apache Flink.

Request Syntax

```
{
   "ApplicationName": "string",
   "Limit": number,
   "NextToken": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application for which you want to list all versions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Limit

The maximum number of versions to list in this invocation of the operation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

If a previous invocation of this operation returned a pagination token, pass it into this value to retrieve the next set of results. For more information about pagination, see Using the Amazon Command Line Interface's Pagination Options.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Response Syntax

```
{
   "ApplicationVersionSummaries": [
      {
         "ApplicationStatus": "string",
         "ApplicationVersionId": number
      }
   ],
   "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationVersionSummaries

A list of the application versions and the associated configuration summaries. The list includes application versions that were rolled back.

To get the complete description of a specific application version, invoke the DescribeApplicationVersion operation.

Type: Array of ApplicationVersionSummary objects

NextToken

The pagination token for the next set of results, or `null` if there are no additional results. To retrieve the next set of items, pass this token into a subsequent invocation of this operation. For more information about pagination, see Using the Amazon Command Line Interface's Pagination Options.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Errors

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

ListTagsForResource

Retrieves the list of key-value tags assigned to the application. For more information, see Using Tagging.

Request Syntax

```
{
   "ResourceARN": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceARN

The ARN of the application for which to retrieve tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

Response Syntax

```
{
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The key-value tags assigned to the application.

Type: Array of Tag objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

RollbackApplication

Reverts the application to the previous running version. You can roll back an application if you suspect it is stuck in a transient status or in the running status.

You can roll back an application only if it is in the `UPDATING`, `AUTOSCALING`, or `RUNNING` statuses.

When you rollback an application, it loads state data from the last successful snapshot. If the application has no snapshots, Managed Service for Apache Flink rejects the rollback request.

Request Syntax

```
{
   "ApplicationName": "string",
   "CurrentApplicationVersionId": number
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CurrentApplicationVersionId

The current application version ID. You can retrieve the application version ID using DescribeApplication.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

Response Syntax

```
{
   "ApplicationDetail": {
      "ApplicationARN": "string",
      "ApplicationConfigurationDescription": {
         "ApplicationCodeConfigurationDescription": {
            "CodeContentDescription": {
               "CodeMD5": "string",
               "CodeSize": number,
               "S3ApplicationCodeLocationDescription": {
                  "BucketARN": "string",
                  "FileKey": "string",
                  "ObjectVersion": "string"
               },
               "TextContent": "string"
            },
            "CodeContentType": "string"
         },
         "ApplicationEncryptionConfigurationDescription": {
            "KeyId": "string",
            "KeyType": "string"
         },
         "ApplicationSnapshotConfigurationDescription": {
            "SnapshotsEnabled": boolean
         },
         "ApplicationSystemRollbackConfigurationDescription": {
            "RollbackEnabled": boolean
         },
         "EnvironmentPropertyDescriptions": {
            "PropertyGroupDescriptions": [
               {
                  "PropertyGroupId": "string",
                  "PropertyMap": {
                     "string" : "string"
                  }
               }
            ]
         },
         "FlinkApplicationConfigurationDescription": {
            "CheckpointConfigurationDescription": {
               "CheckpointingEnabled": boolean,
               "CheckpointInterval": number,
```

```
            "ConfigurationType": "string",
            "MinPauseBetweenCheckpoints": number
         },
         "JobPlanDescription": "string",
         "MonitoringConfigurationDescription": {
            "ConfigurationType": "string",
            "LogLevel": "string",
            "MetricsLevel": "string"
         },
         "ParallelismConfigurationDescription": {
            "AutoScalingEnabled": boolean,
            "ConfigurationType": "string",
            "CurrentParallelism": number,
            "Parallelism": number,
            "ParallelismPerKPU": number
         }
      },
      "RunConfigurationDescription": {
         "ApplicationRestoreConfigurationDescription": {
            "ApplicationRestoreType": "string",
            "SnapshotName": "string"
         },
         "FlinkRunConfigurationDescription": {
            "AllowNonRestoredState": boolean
         }
      },
      "SqlApplicationConfigurationDescription": {
         "InputDescriptions": [
            {
               "InAppStreamNames": [ "string" ],
               "InputId": "string",
               "InputParallelism": {
                  "Count": number
               },
               "InputProcessingConfigurationDescription": {
                  "InputLambdaProcessorDescription": {
                     "ResourceARN": "string",
                     "RoleARN": "string"
                  }
               },
               "InputSchema": {
                  "RecordColumns": [
                     {
                        "Mapping": "string",
```

```
                        "Name": "string",
                        "SqlType": "string"
                     }
                  ],
                  "RecordEncoding": "string",
                  "RecordFormat": {
                     "MappingParameters": {
                        "CSVMappingParameters": {
                           "RecordColumnDelimiter": "string",
                           "RecordRowDelimiter": "string"
                        },
                        "JSONMappingParameters": {
                           "RecordRowPath": "string"
                        }
                     },
                     "RecordFormatType": "string"
                  }
               },
               "InputStartingPositionConfiguration": {
                  "InputStartingPosition": "string"
               },
               "KinesisFirehoseInputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "KinesisStreamsInputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "NamePrefix": "string"
            }
         ],
         "OutputDescriptions": [
            {
               "DestinationSchema": {
                  "RecordFormatType": "string"
               },
               "KinesisFirehoseOutputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
               },
               "KinesisStreamsOutputDescription": {
                  "ResourceARN": "string",
                  "RoleARN": "string"
```

```
                },
                "LambdaOutputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "Name": "string",
                "OutputId": "string"
             }
          ],
          "ReferenceDataSourceDescriptions": [
             {
                "ReferenceId": "string",
                "ReferenceSchema": {
                   "RecordColumns": [
                      {
                         "Mapping": "string",
                         "Name": "string",
                         "SqlType": "string"
                      }
                   ],
                   "RecordEncoding": "string",
                   "RecordFormat": {
                      "MappingParameters": {
                         "CSVMappingParameters": {
                            "RecordColumnDelimiter": "string",
                            "RecordRowDelimiter": "string"
                         },
                         "JSONMappingParameters": {
                            "RecordRowPath": "string"
                         }
                      },
                      "RecordFormatType": "string"
                   }
                },
                "S3ReferenceDataSourceDescription": {
                   "BucketARN": "string",
                   "FileKey": "string",
                   "ReferenceRoleARN": "string"
                },
                "TableName": "string"
             }
          ]
       },
       "VpcConfigurationDescriptions": [
```

```
            {
               "SecurityGroupIds": [ "string" ],
               "SubnetIds": [ "string" ],
               "VpcConfigurationId": "string",
               "VpcId": "string"
            }
         ],
         "ZeppelinApplicationConfigurationDescription": {
            "CatalogConfigurationDescription": {
               "GlueDataCatalogConfigurationDescription": {
                  "DatabaseARN": "string"
               }
            },
            "CustomArtifactsConfigurationDescription": [
               {
                  "ArtifactType": "string",
                  "MavenReferenceDescription": {
                     "ArtifactId": "string",
                     "GroupId": "string",
                     "Version": "string"
                  },
                  "S3ContentLocationDescription": {
                     "BucketARN": "string",
                     "FileKey": "string",
                     "ObjectVersion": "string"
                  }
               }
            ],
            "DeployAsApplicationConfigurationDescription": {
               "S3ContentLocationDescription": {
                  "BasePath": "string",
                  "BucketARN": "string"
               }
            },
            "MonitoringConfigurationDescription": {
               "LogLevel": "string"
            }
         }
      },
      "ApplicationDescription": "string",
      "ApplicationMaintenanceConfigurationDescription": {
         "ApplicationMaintenanceWindowEndTime": "string",
         "ApplicationMaintenanceWindowStartTime": "string"
      },
```

```
        "ApplicationMode": "string",
        "ApplicationName": "string",
        "ApplicationStatus": "string",
        "ApplicationVersionCreateTimestamp": number,
        "ApplicationVersionId": number,
        "ApplicationVersionRolledBackFrom": number,
        "ApplicationVersionRolledBackTo": number,
        "ApplicationVersionUpdatedFrom": number,
        "CloudWatchLoggingOptionDescriptions": [
           {
              "CloudWatchLoggingOptionId": "string",
              "LogStreamARN": "string",
              "RoleARN": "string"
           }
        ],
        "ConditionalToken": "string",
        "CreateTimestamp": number,
        "LastUpdateTimestamp": number,
        "RuntimeEnvironment": "string",
        "ServiceExecutionRole": "string"
    },
    "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationDetail

Describes the application, including the application Amazon Resource Name (ARN), status, latest version, and input and output configurations.

Type: ApplicationDetail object

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

StartApplication

Starts the specified Managed Service for Apache Flink application. After creating an application, you must exclusively call this operation to start your application.

Request Syntax

```
{
   "ApplicationName": "string",
   "RunConfiguration": {
      "ApplicationRestoreConfiguration": {
         "ApplicationRestoreType": "string",
         "SnapshotName": "string"
      },
      "FlinkRunConfiguration": {
         "AllowNonRestoredState": boolean
      },
      "SqlRunConfigurations": [
         {
            "InputId": "string",
            "InputStartingPositionConfiguration": {
               "InputStartingPosition": "string"
            }
         }
      ]
   }
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

RunConfiguration

Identifies the run configuration (start parameters) of a Managed Service for Apache Flink application.

Type: RunConfiguration object

Required: No

Response Syntax

```
{
   "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

StopApplication

Stops the application from processing data. You can stop an application only if it is in the running status, unless you set the `Force` parameter to `true`.

You can use the DescribeApplication operation to find the application status.

Managed Service for Apache Flink takes a snapshot when the application is stopped, unless `Force` is set to `true`.

Request Syntax

```
{
   "ApplicationName": "string",
   "Force": boolean
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationName

The name of the running application to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Force

Set to `true` to force the application to stop. If you set `Force` to `true`, Managed Service for Apache Flink stops the application without taking a snapshot.

> **Note**
>
> Force-stopping your application may lead to data loss or duplication. To prevent data loss or duplicate processing of data during application restarts, we recommend you to take frequent snapshots of your application.

You can only force stop a Managed Service for Apache Flink application. You can't force stop a SQL-based Kinesis Data Analytics application.

The application must be in the `STARTING`, `UPDATING`, `STOPPING`, `AUTOSCALING`, or `RUNNING` status.

Type: Boolean

Required: No

Response Syntax

```
{
   "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2

- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

TagResource

Adds one or more key-value tags to a Managed Service for Apache Flink application. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50. For more information, see Using Tagging.

Request Syntax

```
{
   "ResourceARN": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ]
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceARN

The ARN of the application to assign the tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

Tags

The key-value tags to assign to the application.

Type: Array of Tag objects

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

TooManyTagsException

Application created with too many tags, or too many tags added to an application. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

UntagResource

Removes one or more tags from a Managed Service for Apache Flink application. For more information, see Using Tagging.

Request Syntax

```
{
   "ResourceARN": "string",
   "TagKeys": [ "string" ]
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceARN

The ARN of the Managed Service for Apache Flink application from which to remove the tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

TagKeys

A list of keys of tags to remove from the specified application.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

TooManyTagsException

Application created with too many tags, or too many tags added to an application. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

UpdateApplication

Updates an existing Managed Service for Apache Flink application. Using this operation, you can update application code, input configuration, and output configuration.

Managed Service for Apache Flink updates the `ApplicationVersionId` each time you update your application.

Request Syntax

```
{
   "ApplicationConfigurationUpdate": {
      "ApplicationCodeConfigurationUpdate": {
         "CodeContentTypeUpdate": "string",
         "CodeContentUpdate": {
            "S3ContentLocationUpdate": {
               "BucketARNUpdate": "string",
               "FileKeyUpdate": "string",
               "ObjectVersionUpdate": "string"
            },
            "TextContentUpdate": "string",
            "ZipFileContentUpdate": blob
         }
      },
      "ApplicationEncryptionConfigurationUpdate": {
         "KeyIdUpdate": "string",
         "KeyTypeUpdate": "string"
      },
      "ApplicationSnapshotConfigurationUpdate": {
         "SnapshotsEnabledUpdate": boolean
      },
      "ApplicationSystemRollbackConfigurationUpdate": {
         "RollbackEnabledUpdate": boolean
      },
      "EnvironmentPropertyUpdates": {
         "PropertyGroups": [
            {
               "PropertyGroupId": "string",
               "PropertyMap": {
                  "string" : "string"
               }
            }
         ]
```

```
        },
        "FlinkApplicationConfigurationUpdate": {
           "CheckpointConfigurationUpdate": {
              "CheckpointingEnabledUpdate": boolean,
              "CheckpointIntervalUpdate": number,
              "ConfigurationTypeUpdate": "string",
              "MinPauseBetweenCheckpointsUpdate": number
           },
           "MonitoringConfigurationUpdate": {
              "ConfigurationTypeUpdate": "string",
              "LogLevelUpdate": "string",
              "MetricsLevelUpdate": "string"
           },
           "ParallelismConfigurationUpdate": {
              "AutoScalingEnabledUpdate": boolean,
              "ConfigurationTypeUpdate": "string",
              "ParallelismPerKPUUpdate": number,
              "ParallelismUpdate": number
           }
        },
        "SqlApplicationConfigurationUpdate": {
           "InputUpdates": [
              {
                 "InputId": "string",
                 "InputParallelismUpdate": {
                    "CountUpdate": number
                 },
                 "InputProcessingConfigurationUpdate": {
                    "InputLambdaProcessorUpdate": {
                       "ResourceARNUpdate": "string"
                    }
                 },
                 "InputSchemaUpdate": {
                    "RecordColumnUpdates": [
                       {
                          "Mapping": "string",
                          "Name": "string",
                          "SqlType": "string"
                       }
                    ],
                    "RecordEncodingUpdate": "string",
                    "RecordFormatUpdate": {
                       "MappingParameters": {
                          "CSVMappingParameters": {
```

```
                        "RecordColumnDelimiter": "string",
                        "RecordRowDelimiter": "string"
                    },
                    "JSONMappingParameters": {
                        "RecordRowPath": "string"
                    }
                },
                "RecordFormatType": "string"
            }
        },
        "KinesisFirehoseInputUpdate": {
            "ResourceARNUpdate": "string"
        },
        "KinesisStreamsInputUpdate": {
            "ResourceARNUpdate": "string"
        },
        "NamePrefixUpdate": "string"
    }
],
"OutputUpdates": [
    {
        "DestinationSchemaUpdate": {
            "RecordFormatType": "string"
        },
        "KinesisFirehoseOutputUpdate": {
            "ResourceARNUpdate": "string"
        },
        "KinesisStreamsOutputUpdate": {
            "ResourceARNUpdate": "string"
        },
        "LambdaOutputUpdate": {
            "ResourceARNUpdate": "string"
        },
        "NameUpdate": "string",
        "OutputId": "string"
    }
],
"ReferenceDataSourceUpdates": [
    {
        "ReferenceId": "string",
        "ReferenceSchemaUpdate": {
            "RecordColumns": [
                {
                    "Mapping": "string",
```

```
                        "Name": "string",
                        "SqlType": "string"
                     }
                  ],
                  "RecordEncoding": "string",
                  "RecordFormat": {
                     "MappingParameters": {
                        "CSVMappingParameters": {
                           "RecordColumnDelimiter": "string",
                           "RecordRowDelimiter": "string"
                        },
                        "JSONMappingParameters": {
                           "RecordRowPath": "string"
                        }
                     },
                     "RecordFormatType": "string"
                  }
               },
               "S3ReferenceDataSourceUpdate": {
                  "BucketARNUpdate": "string",
                  "FileKeyUpdate": "string"
               },
               "TableNameUpdate": "string"
            }
         ]
      },
      "VpcConfigurationUpdates": [
         {
            "SecurityGroupIdUpdates": [ "string" ],
            "SubnetIdUpdates": [ "string" ],
            "VpcConfigurationId": "string"
         }
      ],
      "ZeppelinApplicationConfigurationUpdate": {
         "CatalogConfigurationUpdate": {
            "GlueDataCatalogConfigurationUpdate": {
               "DatabaseARNUpdate": "string"
            }
         },
         "CustomArtifactsConfigurationUpdate": [
            {
               "ArtifactType": "string",
               "MavenReference": {
                  "ArtifactId": "string",
```

```
                    "GroupId": "string",
                    "Version": "string"
                },
                "S3ContentLocation": {
                    "BucketARN": "string",
                    "FileKey": "string",
                    "ObjectVersion": "string"
                }
            }
        ],
        "DeployAsApplicationConfigurationUpdate": {
            "S3ContentLocationUpdate": {
                "BasePathUpdate": "string",
                "BucketARNUpdate": "string"
            }
        },
        "MonitoringConfigurationUpdate": {
            "LogLevelUpdate": "string"
        }
    }
  },
  "ApplicationName": "string",
  "CloudWatchLoggingOptionUpdates": [
    {
        "CloudWatchLoggingOptionId": "string",
        "LogStreamARNUpdate": "string"
    }
  ],
  "ConditionalToken": "string",
  "CurrentApplicationVersionId": number,
  "RunConfigurationUpdate": {
    "ApplicationRestoreConfiguration": {
        "ApplicationRestoreType": "string",
        "SnapshotName": "string"
    },
    "FlinkRunConfiguration": {
        "AllowNonRestoredState": boolean
    }
  },
  "RuntimeEnvironmentUpdate": "string",
  "ServiceExecutionRoleUpdate": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationConfigurationUpdate

Describes application configuration updates.

Type: ApplicationConfigurationUpdate object

Required: No

ApplicationName

The name of the application to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

CloudWatchLoggingOptionUpdates

Describes application Amazon CloudWatch logging option updates. You can only update existing CloudWatch logging options with this action. To add a new CloudWatch logging option, use AddApplicationCloudWatchLoggingOption.

Type: Array of CloudWatchLoggingOptionUpdate objects

Required: No

ConditionalToken

A value you use to implement strong concurrency for application updates. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`. You get the application's current `ConditionalToken` using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CurrentApplicationVersionId

The current application version ID. You must provide the `CurrentApplicationVersionId` or the `ConditionalToken`.You can retrieve the application version ID using DescribeApplication. For better concurrency support, use the `ConditionalToken` parameter instead of `CurrentApplicationVersionId`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

RunConfigurationUpdate

Describes updates to the application's starting parameters.

Type: RunConfigurationUpdate object

Required: No

RuntimeEnvironmentUpdate

Updates the Managed Service for Apache Flink runtime environment used to run your code. To avoid issues you must:

- Ensure your new jar and dependencies are compatible with the new runtime selected.
- Ensure your new code's state is compatible with the snapshot from which your application will start

Type: String

Valid Values: `SQL-1_0 | FLINK-1_6 | FLINK-1_8 | ZEPPELIN-FLINK-1_0 | FLINK-1_11 | FLINK-1_13 | ZEPPELIN-FLINK-2_0 | FLINK-1_15 | ZEPPELIN-FLINK-3_0 | FLINK-1_18 | FLINK-1_19 | FLINK-1_20`

Required: No

ServiceExecutionRoleUpdate

Describes updates to the service execution role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

Response Syntax

```
{
   "ApplicationDetail": {
      "ApplicationARN": "string",
      "ApplicationConfigurationDescription": {
         "ApplicationCodeConfigurationDescription": {
            "CodeContentDescription": {
               "CodeMD5": "string",
               "CodeSize": number,
               "S3ApplicationCodeLocationDescription": {
                  "BucketARN": "string",
                  "FileKey": "string",
                  "ObjectVersion": "string"
               },
               "TextContent": "string"
            },
            "CodeContentType": "string"
         },
         "ApplicationEncryptionConfigurationDescription": {
            "KeyId": "string",
            "KeyType": "string"
         },
         "ApplicationSnapshotConfigurationDescription": {
            "SnapshotsEnabled": boolean
         },
         "ApplicationSystemRollbackConfigurationDescription": {
            "RollbackEnabled": boolean
         },
         "EnvironmentPropertyDescriptions": {
            "PropertyGroupDescriptions": [
               {
                  "PropertyGroupId": "string",
                  "PropertyMap": {
                     "string" : "string"
                  }
               }
            ]
         },
```

```
            "FlinkApplicationConfigurationDescription": {
               "CheckpointConfigurationDescription": {
                  "CheckpointingEnabled": boolean,
                  "CheckpointInterval": number,
                  "ConfigurationType": "string",
                  "MinPauseBetweenCheckpoints": number
               },
               "JobPlanDescription": "string",
               "MonitoringConfigurationDescription": {
                  "ConfigurationType": "string",
                  "LogLevel": "string",
                  "MetricsLevel": "string"
               },
               "ParallelismConfigurationDescription": {
                  "AutoScalingEnabled": boolean,
                  "ConfigurationType": "string",
                  "CurrentParallelism": number,
                  "Parallelism": number,
                  "ParallelismPerKPU": number
               }
            },
            "RunConfigurationDescription": {
               "ApplicationRestoreConfigurationDescription": {
                  "ApplicationRestoreType": "string",
                  "SnapshotName": "string"
               },
               "FlinkRunConfigurationDescription": {
                  "AllowNonRestoredState": boolean
               }
            },
            "SqlApplicationConfigurationDescription": {
               "InputDescriptions": [
                  {
                     "InAppStreamNames": [ "string" ],
                     "InputId": "string",
                     "InputParallelism": {
                        "Count": number
                     },
                     "InputProcessingConfigurationDescription": {
                        "InputLambdaProcessorDescription": {
                           "ResourceARN": "string",
                           "RoleARN": "string"
                        }
                     },
```

```
                "InputSchema": {
                   "RecordColumns": [
                      {
                         "Mapping": "string",
                         "Name": "string",
                         "SqlType": "string"
                      }
                   ],
                   "RecordEncoding": "string",
                   "RecordFormat": {
                      "MappingParameters": {
                         "CSVMappingParameters": {
                            "RecordColumnDelimiter": "string",
                            "RecordRowDelimiter": "string"
                         },
                         "JSONMappingParameters": {
                            "RecordRowPath": "string"
                         }
                      },
                      "RecordFormatType": "string"
                   }
                },
                "InputStartingPositionConfiguration": {
                   "InputStartingPosition": "string"
                },
                "KinesisFirehoseInputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "KinesisStreamsInputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "NamePrefix": "string"
             }
          ],
          "OutputDescriptions": [
             {
                "DestinationSchema": {
                   "RecordFormatType": "string"
                },
                "KinesisFirehoseOutputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
```

```
                },
                "KinesisStreamsOutputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "LambdaOutputDescription": {
                   "ResourceARN": "string",
                   "RoleARN": "string"
                },
                "Name": "string",
                "OutputId": "string"
             }
          ],
          "ReferenceDataSourceDescriptions": [
             {
                "ReferenceId": "string",
                "ReferenceSchema": {
                   "RecordColumns": [
                      {
                         "Mapping": "string",
                         "Name": "string",
                         "SqlType": "string"
                      }
                   ],
                   "RecordEncoding": "string",
                   "RecordFormat": {
                      "MappingParameters": {
                         "CSVMappingParameters": {
                            "RecordColumnDelimiter": "string",
                            "RecordRowDelimiter": "string"
                         },
                         "JSONMappingParameters": {
                            "RecordRowPath": "string"
                         }
                      },
                      "RecordFormatType": "string"
                   }
                },
                "S3ReferenceDataSourceDescription": {
                   "BucketARN": "string",
                   "FileKey": "string",
                   "ReferenceRoleARN": "string"
                },
                "TableName": "string"
```

```
                }
            ]
        },
        "VpcConfigurationDescriptions": [
            {
                "SecurityGroupIds": [ "string" ],
                "SubnetIds": [ "string" ],
                "VpcConfigurationId": "string",
                "VpcId": "string"
            }
        ],
        "ZeppelinApplicationConfigurationDescription": {
            "CatalogConfigurationDescription": {
                "GlueDataCatalogConfigurationDescription": {
                    "DatabaseARN": "string"
                }
            },
            "CustomArtifactsConfigurationDescription": [
                {
                    "ArtifactType": "string",
                    "MavenReferenceDescription": {
                        "ArtifactId": "string",
                        "GroupId": "string",
                        "Version": "string"
                    },
                    "S3ContentLocationDescription": {
                        "BucketARN": "string",
                        "FileKey": "string",
                        "ObjectVersion": "string"
                    }
                }
            ],
            "DeployAsApplicationConfigurationDescription": {
                "S3ContentLocationDescription": {
                    "BasePath": "string",
                    "BucketARN": "string"
                }
            },
            "MonitoringConfigurationDescription": {
                "LogLevel": "string"
            }
        }
    },
    "ApplicationDescription": "string",
```

```
        "ApplicationMaintenanceConfigurationDescription": {
           "ApplicationMaintenanceWindowEndTime": "string",
           "ApplicationMaintenanceWindowStartTime": "string"
        },
        "ApplicationMode": "string",
        "ApplicationName": "string",
        "ApplicationStatus": "string",
        "ApplicationVersionCreateTimestamp": number,
        "ApplicationVersionId": number,
        "ApplicationVersionRolledBackFrom": number,
        "ApplicationVersionRolledBackTo": number,
        "ApplicationVersionUpdatedFrom": number,
        "CloudWatchLoggingOptionDescriptions": [
           {
              "CloudWatchLoggingOptionId": "string",
              "LogStreamARN": "string",
              "RoleARN": "string"
           }
        ],
        "ConditionalToken": "string",
        "CreateTimestamp": number,
        "LastUpdateTimestamp": number,
        "RuntimeEnvironment": "string",
        "ServiceExecutionRole": "string"
    },
    "OperationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationDetail

Describes application updates.

Type: ApplicationDetail object

OperationId

The operation ID that can be used to track the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

CodeValidationException

The user-provided application code (query) is not valid. This can be a simple syntax error.

HTTP Status Code: 400

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidApplicationConfigurationException

The user-provided application configuration is not valid.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

InvalidRequestException

The request JSON is not valid for the operation.

HTTP Status Code: 400

LimitExceededException

The number of allowed resources has been exceeded.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

UpdateApplicationMaintenanceConfiguration

Updates the maintenance configuration of the Managed Service for Apache Flink application.

You can invoke this operation on an application that is in one of the two following states: `READY` or `RUNNING`. If you invoke it when the application is in a state other than these two states, it throws a `ResourceInUseException`. The service makes use of the updated configuration the next time it schedules maintenance for the application. If you invoke this operation after the service schedules maintenance, the service will apply the configuration update the next time it schedules maintenance for the application. This means that you might not see the maintenance configuration update applied to the maintenance process that follows a successful invocation of this operation, but to the following maintenance process instead.

To see the current maintenance configuration of your application, invoke the DescribeApplication operation.

For information about application maintenance, see Managed Service for Apache Flink for Apache Flink Maintenance.

> **Note**
>
> This operation is supported only for Managed Service for Apache Flink.

Request Syntax

```
{
   "ApplicationMaintenanceConfigurationUpdate": {
      "ApplicationMaintenanceWindowStartTimeUpdate": "string"
   },
   "ApplicationName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationMaintenanceConfigurationUpdate

Describes the application maintenance configuration update.

Type: ApplicationMaintenanceConfigurationUpdate object

Required: Yes

ApplicationName

The name of the application for which you want to update the maintenance configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Syntax

```
{
   "ApplicationARN": "string",
   "ApplicationMaintenanceConfigurationDescription": {
      "ApplicationMaintenanceWindowEndTime": "string",
      "ApplicationMaintenanceWindowStartTime": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationARN

The Amazon Resource Name (ARN) of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

ApplicationMaintenanceConfigurationDescription

The application maintenance configuration description after the update.

Type: ApplicationMaintenanceConfigurationDescription object

Errors

ConcurrentModificationException

Exception thrown as a result of concurrent modifications to an application. This error can be the result of attempting to modify an application without using the current application ID.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter value is not valid.

HTTP Status Code: 400

ResourceInUseException

The application is not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

Specified application can't be found.

HTTP Status Code: 400

UnsupportedOperationException

The request was rejected because a specified parameter is not supported or a specified resource is not valid for this operation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET V4
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python (Boto3)
- AWS SDK for Ruby V3

Data Types

The Amazon Kinesis Analytics API contains several data types that various actions use. This section describes each data type in detail.

> **Note**
>
> The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- ApplicationCodeConfiguration
- ApplicationCodeConfigurationDescription
- ApplicationCodeConfigurationUpdate
- ApplicationConfiguration
- ApplicationConfigurationDescription
- ApplicationConfigurationUpdate
- ApplicationDetail
- ApplicationEncryptionConfiguration
- ApplicationEncryptionConfigurationDescription
- ApplicationEncryptionConfigurationUpdate
- ApplicationMaintenanceConfigurationDescription
- ApplicationMaintenanceConfigurationUpdate
- ApplicationOperationInfo
- ApplicationOperationInfoDetails
- ApplicationRestoreConfiguration
- ApplicationSnapshotConfiguration
- ApplicationSnapshotConfigurationDescription
- ApplicationSnapshotConfigurationUpdate
- ApplicationSummary
- ApplicationSystemRollbackConfiguration

- ApplicationSystemRollbackConfigurationDescription
- ApplicationSystemRollbackConfigurationUpdate
- ApplicationVersionChangeDetails
- ApplicationVersionSummary
- CatalogConfiguration
- CatalogConfigurationDescription
- CatalogConfigurationUpdate
- CheckpointConfiguration
- CheckpointConfigurationDescription
- CheckpointConfigurationUpdate
- CloudWatchLoggingOption
- CloudWatchLoggingOptionDescription
- CloudWatchLoggingOptionUpdate
- CodeContent
- CodeContentDescription
- CodeContentUpdate
- CSVMappingParameters
- CustomArtifactConfiguration
- CustomArtifactConfigurationDescription
- DeployAsApplicationConfiguration
- DeployAsApplicationConfigurationDescription
- DeployAsApplicationConfigurationUpdate
- DestinationSchema
- EnvironmentProperties
- EnvironmentPropertyDescriptions
- EnvironmentPropertyUpdates
- ErrorInfo
- FlinkApplicationConfiguration
- FlinkApplicationConfigurationDescription
- FlinkApplicationConfigurationUpdate

- FlinkRunConfiguration
- GlueDataCatalogConfiguration
- GlueDataCatalogConfigurationDescription
- GlueDataCatalogConfigurationUpdate
- Input
- InputDescription
- InputLambdaProcessor
- InputLambdaProcessorDescription
- InputLambdaProcessorUpdate
- InputParallelism
- InputParallelismUpdate
- InputProcessingConfiguration
- InputProcessingConfigurationDescription
- InputProcessingConfigurationUpdate
- InputSchemaUpdate
- InputStartingPositionConfiguration
- InputUpdate
- JSONMappingParameters
- KinesisFirehoseInput
- KinesisFirehoseInputDescription
- KinesisFirehoseInputUpdate
- KinesisFirehoseOutput
- KinesisFirehoseOutputDescription
- KinesisFirehoseOutputUpdate
- KinesisStreamsInput
- KinesisStreamsInputDescription
- KinesisStreamsInputUpdate
- KinesisStreamsOutput
- KinesisStreamsOutputDescription
- KinesisStreamsOutputUpdate

- LambdaOutput
- LambdaOutputDescription
- LambdaOutputUpdate
- MappingParameters
- MavenReference
- MonitoringConfiguration
- MonitoringConfigurationDescription
- MonitoringConfigurationUpdate
- OperationFailureDetails
- Output
- OutputDescription
- OutputUpdate
- ParallelismConfiguration
- ParallelismConfigurationDescription
- ParallelismConfigurationUpdate
- PropertyGroup
- RecordColumn
- RecordFormat
- ReferenceDataSource
- ReferenceDataSourceDescription
- ReferenceDataSourceUpdate
- RunConfiguration
- RunConfigurationDescription
- RunConfigurationUpdate
- S3ApplicationCodeLocationDescription
- S3Configuration
- S3ContentBaseLocation
- S3ContentBaseLocationDescription
- S3ContentBaseLocationUpdate
- S3ContentLocation

- S3ContentLocationUpdate
- S3ReferenceDataSource
- S3ReferenceDataSourceDescription
- S3ReferenceDataSourceUpdate
- SnapshotDetails
- SourceSchema
- SqlApplicationConfiguration
- SqlApplicationConfigurationDescription
- SqlApplicationConfigurationUpdate
- SqlRunConfiguration
- Tag
- VpcConfiguration
- VpcConfigurationDescription
- VpcConfigurationUpdate
- ZeppelinApplicationConfiguration
- ZeppelinApplicationConfigurationDescription
- ZeppelinApplicationConfigurationUpdate
- ZeppelinMonitoringConfiguration
- ZeppelinMonitoringConfigurationDescription
- ZeppelinMonitoringConfigurationUpdate

ApplicationCodeConfiguration

Describes code configuration for an application.

Contents

CodeContentType

Specifies whether the code content is in text or zip format.

Type: String

Valid Values: `PLAINTEXT | ZIPFILE`

Required: Yes

CodeContent

The location and type of the application code.

Type: CodeContent object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationCodeConfigurationDescription

Describes code configuration for an application.

Contents

CodeContentType

Specifies whether the code content is in text or zip format.

Type: String

Valid Values: `PLAINTEXT | ZIPFILE`

Required: Yes

CodeContentDescription

Describes details about the location and format of the application code.

Type: CodeContentDescription object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationCodeConfigurationUpdate

Describes code configuration updates for an application. This is supported for a Managed Service for Apache Flink application or a SQL-based Kinesis Data Analytics application.

Contents

CodeContentTypeUpdate

Describes updates to the code content type.

Type: String

Valid Values: `PLAINTEXT | ZIPFILE`

Required: No

CodeContentUpdate

Describes updates to the code content of an application.

Type: CodeContentUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationConfiguration

Specifies the creation parameters for a Managed Service for Apache Flink application.

Contents

ApplicationCodeConfiguration

The code location and type parameters for a Managed Service for Apache Flink application.

Type: ApplicationCodeConfiguration object

Required: No

ApplicationEncryptionConfiguration

The configuration to manage encryption at rest.

Type: ApplicationEncryptionConfiguration object

Required: No

ApplicationSnapshotConfiguration

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSnapshotConfiguration object

Required: No

ApplicationSystemRollbackConfiguration

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSystemRollbackConfiguration object

Required: No

EnvironmentProperties

Describes execution properties for a Managed Service for Apache Flink application.

Type: EnvironmentProperties object

Required: No

FlinkApplicationConfiguration

The creation and update parameters for a Managed Service for Apache Flink application.

Type: FlinkApplicationConfiguration object

Required: No

SqlApplicationConfiguration

The creation and update parameters for a SQL-based Kinesis Data Analytics application.

Type: SqlApplicationConfiguration object

Required: No

VpcConfigurations

The array of descriptions of VPC configurations available to the application.

Type: Array of VpcConfiguration objects

Required: No

ZeppelinApplicationConfiguration

The configuration parameters for a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinApplicationConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationConfigurationDescription

Describes details about the application code and starting parameters for a Managed Service for Apache Flink application.

Contents

ApplicationCodeConfigurationDescription

The details about the application code for a Managed Service for Apache Flink application.

Type: ApplicationCodeConfigurationDescription object

Required: No

ApplicationEncryptionConfigurationDescription

Describes the encryption at rest configuration.

Type: ApplicationEncryptionConfigurationDescription object

Required: No

ApplicationSnapshotConfigurationDescription

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSnapshotConfigurationDescription object

Required: No

ApplicationSystemRollbackConfigurationDescription

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSystemRollbackConfigurationDescription object

Required: No

EnvironmentPropertyDescriptions

Describes execution properties for a Managed Service for Apache Flink application.

Type: EnvironmentPropertyDescriptions object

Required: No

FlinkApplicationConfigurationDescription

The details about a Managed Service for Apache Flink application.

Type: FlinkApplicationConfigurationDescription object

Required: No

RunConfigurationDescription

The details about the starting properties for a Managed Service for Apache Flink application.

Type: RunConfigurationDescription object

Required: No

SqlApplicationConfigurationDescription

The details about inputs, outputs, and reference data sources for a SQL-based Kinesis Data Analytics application.

Type: SqlApplicationConfigurationDescription object

Required: No

VpcConfigurationDescriptions

The array of descriptions of VPC configurations available to the application.

Type: Array of VpcConfigurationDescription objects

Required: No

ZeppelinApplicationConfigurationDescription

The configuration parameters for a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinApplicationConfigurationDescription object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationConfigurationUpdate

Describes updates to an application's configuration.

Contents

ApplicationCodeConfigurationUpdate

Describes updates to an application's code configuration.

Type: ApplicationCodeConfigurationUpdate object

Required: No

ApplicationEncryptionConfigurationUpdate

Represents an update for encryption at rest configuration.

Type: ApplicationEncryptionConfigurationUpdate object

Required: No

ApplicationSnapshotConfigurationUpdate

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSnapshotConfigurationUpdate object

Required: No

ApplicationSystemRollbackConfigurationUpdate

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: ApplicationSystemRollbackConfigurationUpdate object

Required: No

EnvironmentPropertyUpdates

Describes updates to the environment properties for a Managed Service for Apache Flink application.

Type: EnvironmentPropertyUpdates object

Required: No

FlinkApplicationConfigurationUpdate

Describes updates to a Managed Service for Apache Flink application's configuration.

Type: FlinkApplicationConfigurationUpdate object

Required: No

SqlApplicationConfigurationUpdate

Describes updates to a SQL-based Kinesis Data Analytics application's configuration.

Type: SqlApplicationConfigurationUpdate object

Required: No

VpcConfigurationUpdates

Updates to the array of descriptions of VPC configurations available to the application.

Type: Array of VpcConfigurationUpdate objects

Required: No

ZeppelinApplicationConfigurationUpdate

Updates to the configuration of a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinApplicationConfigurationUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationDetail

Describes the application, including the application Amazon Resource Name (ARN), status, latest version, and input and output configurations.

Contents

ApplicationARN

The ARN of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ApplicationStatus

The status of the application.

Type: String

Valid Values: `DELETING | STARTING | STOPPING | READY | RUNNING | UPDATING | AUTOSCALING | FORCE_STOPPING | ROLLING_BACK | MAINTENANCE | ROLLED_BACK`

Required: Yes

ApplicationVersionId

Provides the current application version. Managed Service for Apache Flink updates the `ApplicationVersionId` each time you update the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

RuntimeEnvironment

The runtime environment for the application.

Type: String

Valid Values: `SQL-1_0 | FLINK-1_6 | FLINK-1_8 | ZEPPELIN-FLINK-1_0 | FLINK-1_11 | FLINK-1_13 | ZEPPELIN-FLINK-2_0 | FLINK-1_15 | ZEPPELIN-FLINK-3_0 | FLINK-1_18 | FLINK-1_19 | FLINK-1_20`

Required: Yes

ApplicationConfigurationDescription

Describes details about the application code and starting parameters for a Managed Service for Apache Flink application.

Type: ApplicationConfigurationDescription object

Required: No

ApplicationDescription

The description of the application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ApplicationMaintenanceConfigurationDescription

The details of the maintenance configuration for the application.

Type: ApplicationMaintenanceConfigurationDescription object

Required: No

ApplicationMode

To create a Managed Service for Apache Flink Studio notebook, you must set the mode to `INTERACTIVE`. However, for a Managed Service for Apache Flink application, the mode is optional.

Type: String

Valid Values: `STREAMING | INTERACTIVE`

Required: No

ApplicationVersionCreateTimestamp

The timestamp that indicates when the application version was created.

Type: Timestamp

Required: No

ApplicationVersionRolledBackFrom

If you reverted the application using RollbackApplication, the application version when `RollbackApplication` was called.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

ApplicationVersionRolledBackTo

The version to which you want to roll back the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

ApplicationVersionUpdatedFrom

The previous application version before the latest application update. RollbackApplication reverts the application to this version.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: No

CloudWatchLoggingOptionDescriptions

Describes the application Amazon CloudWatch logging options.

Type: Array of CloudWatchLoggingOptionDescription objects

Required: No

ConditionalToken

A value you use to implement strong concurrency for application updates.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_+/=]+`

Required: No

CreateTimestamp

The current timestamp when the application was created.

Type: Timestamp

Required: No

LastUpdateTimestamp

The current timestamp when the application was last updated.

Type: Timestamp

Required: No

ServiceExecutionRole

Specifies the IAM role that the application uses to access external resources.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationEncryptionConfiguration

Specifies the configuration to manage encryption at rest.

Contents

KeyType

Specifies the type of key used for encryption at rest.

Type: String

Valid Values: `AWS_OWNED_KEY | CUSTOMER_MANAGED_KEY`

Required: Yes

KeyId

The key ARN, key ID, alias ARN, or alias name of the KMS key used for encryption at rest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationEncryptionConfigurationDescription

Describes the encryption at rest configuration.

Contents

KeyType

Specifies the type of key used for encryption at rest.

Type: String

Valid Values: `AWS_OWNED_KEY | CUSTOMER_MANAGED_KEY`

Required: Yes

KeyId

The key ARN, key ID, alias ARN, or alias name of the KMS key used for encryption at rest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationEncryptionConfigurationUpdate

Describes configuration updates to encryption at rest.

Contents

KeyTypeUpdate

Specifies the type of key to be used for encryption at rest.

Type: String

Valid Values: `AWS_OWNED_KEY | CUSTOMER_MANAGED_KEY`

Required: Yes

KeyIdUpdate

The key ARN, key ID, alias ARN, or alias name of the KMS key to be used for encryption at rest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationMaintenanceConfigurationDescription

The details of the maintenance configuration for the application.

Contents

ApplicationMaintenanceWindowEndTime

The end time for the maintenance window.

Type: String

Length Constraints: Fixed length of 5.

Pattern: `([01][0-9]|2[0-3]):[0-5][0-9]`

Required: Yes

ApplicationMaintenanceWindowStartTime

The start time for the maintenance window.

Type: String

Length Constraints: Fixed length of 5.

Pattern: `([01][0-9]|2[0-3]):[0-5][0-9]`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationMaintenanceConfigurationUpdate

Describes the updated maintenance configuration for the application.

Contents

ApplicationMaintenanceWindowStartTimeUpdate

The updated start time for the maintenance window.

Type: String

Length Constraints: Fixed length of 5.

Pattern: `([01][0-9]|2[0-3]):[0-5][0-9]`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationOperationInfo

A description of the aplication operation that provides information about the updates that were made to the application.

Contents

EndTime

The timestamp that indicates when the operation finished.

Type: Timestamp

Required: No

Operation

The type of operation that is performed on an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

OperationId

The operation ID of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

OperationStatus

The status of the operation.

Type: String

Valid Values: `IN_PROGRESS | CANCELLED | SUCCESSFUL | FAILED`

Required: No

StartTime

The timestamp that indicates when the operation was created.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationOperationInfoDetails

A description of the application operation that provides information about the updates that were made to the application.

Contents

EndTime

The timestamp that indicates when the operation finished.

Type: Timestamp

Required: Yes

Operation

The type of operation that is performed on an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

OperationStatus

The status of the operation.

Type: String

Valid Values: `IN_PROGRESS | CANCELLED | SUCCESSFUL | FAILED`

Required: Yes

StartTime

The timestamp that indicates when the operation was created.

Type: Timestamp

Required: Yes

ApplicationVersionChangeDetails

Contains information about the version changes that the operation applied to the application.

Type: ApplicationVersionChangeDetails object

Required: No

OperationFailureDetails

Provides a description of the operation failure.

Type: OperationFailureDetails object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationRestoreConfiguration

Specifies the method and snapshot to use when restarting an application using previously saved application state.

Contents

ApplicationRestoreType

Specifies how the application should be restored.

Type: String

Valid Values: `SKIP_RESTORE_FROM_SNAPSHOT | RESTORE_FROM_LATEST_SNAPSHOT | RESTORE_FROM_CUSTOM_SNAPSHOT`

Required: Yes

SnapshotName

The identifier of an existing snapshot of application state to use to restart an application. The application uses this value if `RESTORE_FROM_CUSTOM_SNAPSHOT` is specified for the `ApplicationRestoreType`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSnapshotConfiguration

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Contents

SnapshotsEnabled

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSnapshotConfigurationDescription

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Contents

SnapshotsEnabled

Describes whether snapshots are enabled for a Managed Service for Apache Flink application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSnapshotConfigurationUpdate

Describes updates to whether snapshots are enabled for a Managed Service for Apache Flink application.

Contents

SnapshotsEnabledUpdate

Describes updates to whether snapshots are enabled for an application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSummary

Provides application summary information, including the application Amazon Resource Name (ARN), name, and status.

Contents

ApplicationARN

The ARN of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

ApplicationName

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ApplicationStatus

The status of the application.

Type: String

Valid Values: `DELETING | STARTING | STOPPING | READY | RUNNING | UPDATING | AUTOSCALING | FORCE_STOPPING | ROLLING_BACK | MAINTENANCE | ROLLED_BACK`

Required: Yes

ApplicationVersionId

Provides the current application version.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

RuntimeEnvironment

The runtime environment for the application.

Type: String

Valid Values: `SQL-1_0 | FLINK-1_6 | FLINK-1_8 | ZEPPELIN-FLINK-1_0 | FLINK-1_11 | FLINK-1_13 | ZEPPELIN-FLINK-2_0 | FLINK-1_15 | ZEPPELIN-FLINK-3_0 | FLINK-1_18 | FLINK-1_19 | FLINK-1_20`

Required: Yes

ApplicationMode

For a Managed Service for Apache Flink application, the mode is `STREAMING`. For a Managed Service for Apache Flink Studio notebook, it is `INTERACTIVE`.

Type: String

Valid Values: `STREAMING | INTERACTIVE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSystemRollbackConfiguration

Describes the system rollback configuration for a Managed Service for Apache Flink application.

Contents

RollbackEnabled

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSystemRollbackConfigurationDescription

Describes the system rollback configuration for a Managed Service for Apache Flink application.

Contents

RollbackEnabled

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationSystemRollbackConfigurationUpdate

Describes the system rollback configuration for a Managed Service for Apache Flink application.

Contents

RollbackEnabledUpdate

Describes whether system rollbacks are enabled for a Managed Service for Apache Flink application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationVersionChangeDetails

Contains information about the version changes that the operation applied to the application.

Contents

ApplicationVersionUpdatedFrom

The new version that the application was updated to.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

ApplicationVersionUpdatedTo

The version that the operation execution applied to the applicartion.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ApplicationVersionSummary

The summary of the application version.

Contents

ApplicationStatus

The status of the application.

Type: String

Valid Values: `DELETING | STARTING | STOPPING | READY | RUNNING | UPDATING | AUTOSCALING | FORCE_STOPPING | ROLLING_BACK | MAINTENANCE | ROLLED_BACK`

Required: Yes

ApplicationVersionId

The ID of the application version. Managed Service for Apache Flink updates the `ApplicationVersionId` each time you update the application.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CatalogConfiguration

The configuration parameters for the default Amazon Glue database. You use this database for SQL queries that you write in a Managed Service for Apache Flink Studio notebook.

Contents

GlueDataCatalogConfiguration

The configuration parameters for the default Amazon Glue database. You use this database for Apache Flink SQL queries and table API transforms that you write in a Managed Service for Apache Flink Studio notebook.

Type: GlueDataCatalogConfiguration object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CatalogConfigurationDescription

The configuration parameters for the default Amazon Glue database. You use this database for Apache Flink SQL queries and table API transforms that you write in a Managed Service for Apache Flink Studio notebook.

Contents

GlueDataCatalogConfigurationDescription

The configuration parameters for the default Amazon Glue database. You use this database for SQL queries that you write in a Managed Service for Apache Flink Studio notebook.

Type: GlueDataCatalogConfigurationDescription object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CatalogConfigurationUpdate

Updates to the configuration parameters for the default Amazon Glue database. You use this database for SQL queries that you write in a Managed Service for Apache Flink Studio notebook.

Contents

GlueDataCatalogConfigurationUpdate

Updates to the configuration parameters for the default Amazon Glue database. You use this database for SQL queries that you write in a Managed Service for Apache Flink Studio notebook.

Type: GlueDataCatalogConfigurationUpdate object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CheckpointConfiguration

Describes an application's checkpointing configuration. Checkpointing is the process of persisting application state for fault tolerance. For more information, see Checkpoints for Fault Tolerance in the Apache Flink Documentation.

Contents

ConfigurationType

Describes whether the application uses Managed Service for Apache Flink' default checkpointing behavior. You must set this property to `CUSTOM` in order to set the `CheckpointingEnabled`, `CheckpointInterval`, or `MinPauseBetweenCheckpoints` parameters.

> **Note**
>
> If this value is set to `DEFAULT`, the application will use the following values, even if they are set to other values using APIs or application code:
>
> - **CheckpointingEnabled:** true
> - **CheckpointInterval:** 60000
> - **MinPauseBetweenCheckpoints:** 5000

Type: String

Valid Values: `DEFAULT` | `CUSTOM`

Required: Yes

CheckpointingEnabled

Describes whether checkpointing is enabled for a Managed Service for Apache Flink application.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointingEnabled` value of `true`, even if this value is set to another value using this API or in application code.

Type: Boolean

Required: No

CheckpointInterval

Describes the interval in milliseconds between checkpoint operations.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointInterval` value of 60000, even if this value is set to another value using this API or in application code.

Type: Long

Valid Range: Minimum value of 1.

Required: No

MinPauseBetweenCheckpoints

Describes the minimum time in milliseconds after a checkpoint operation completes that a new checkpoint operation can start. If a checkpoint operation takes longer than the `CheckpointInterval`, the application otherwise performs continual checkpoint operations. For more information, see Tuning Checkpointing in the Apache Flink Documentation.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `MinPauseBetweenCheckpoints` value of 5000, even if this value is set using this API or in application code.

Type: Long

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CheckpointConfigurationDescription

Describes checkpointing parameters for a Managed Service for Apache Flink application.

Contents

CheckpointingEnabled

Describes whether checkpointing is enabled for a Managed Service for Apache Flink application.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointingEnabled` value of `true`, even if this value is set to another value using this API or in application code.

Type: Boolean

Required: No

CheckpointInterval

Describes the interval in milliseconds between checkpoint operations.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointInterval` value of 60000, even if this value is set to another value using this API or in application code.

Type: Long

Valid Range: Minimum value of 1.

Required: No

ConfigurationType

Describes whether the application uses the default checkpointing behavior in Managed Service for Apache Flink.

> **Note**
>
> If this value is set to `DEFAULT`, the application will use the following values, even if they are set to other values using APIs or application code:
>
> - **CheckpointingEnabled:** true
> - **CheckpointInterval:** 60000
> - **MinPauseBetweenCheckpoints:** 5000

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

MinPauseBetweenCheckpoints

Describes the minimum time in milliseconds after a checkpoint operation completes that a new checkpoint operation can start.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `MinPauseBetweenCheckpoints` value of 5000, even if this value is set using this API or in application code.

Type: Long

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

CheckpointConfigurationUpdate

Describes updates to the checkpointing parameters for a Managed Service for Apache Flink application.

Contents

CheckpointingEnabledUpdate

Describes updates to whether checkpointing is enabled for an application.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointingEnabled` value of `true`, even if this value is set to another value using this API or in application code.

Type: Boolean

Required: No

CheckpointIntervalUpdate

Describes updates to the interval in milliseconds between checkpoint operations.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `CheckpointInterval` value of 60000, even if this value is set to another value using this API or in application code.

Type: Long

Valid Range: Minimum value of 1.

Required: No

ConfigurationTypeUpdate

Describes updates to whether the application uses the default checkpointing behavior of Managed Service for Apache Flink. You must set this property to `CUSTOM` in order to set the `CheckpointingEnabled`, `CheckpointInterval`, or `MinPauseBetweenCheckpoints` parameters.

> **Note**
>
> If this value is set to `DEFAULT`, the application will use the following values, even if they are set to other values using APIs or application code:
>
> - **CheckpointingEnabled:** true
> - **CheckpointInterval:** 60000
> - **MinPauseBetweenCheckpoints:** 5000

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

MinPauseBetweenCheckpointsUpdate

Describes updates to the minimum time in milliseconds after a checkpoint operation completes that a new checkpoint operation can start.

> **Note**
>
> If `CheckpointConfiguration.ConfigurationType` is `DEFAULT`, the application will use a `MinPauseBetweenCheckpoints` value of 5000, even if this value is set using this API or in application code.

Type: Long

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CloudWatchLoggingOption

Provides a description of Amazon CloudWatch logging options, including the log stream Amazon Resource Name (ARN).

Contents

LogStreamARN

The ARN of the CloudWatch log to receive application messages.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CloudWatchLoggingOptionDescription

Describes the Amazon CloudWatch logging option.

Contents

LogStreamARN

The Amazon Resource Name (ARN) of the CloudWatch log to receive application messages.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

CloudWatchLoggingOptionId

The ID of the CloudWatch logging option description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

RoleARN

The IAM ARN of the role to use to send application messages.

> **Note**
>
> Provided for backward compatibility. Applications created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CloudWatchLoggingOptionUpdate

Describes the Amazon CloudWatch logging option updates.

Contents

CloudWatchLoggingOptionId

The ID of the CloudWatch logging option to update

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

LogStreamARNUpdate

The Amazon Resource Name (ARN) of the CloudWatch log to receive application messages.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CodeContent

Specifies either the application code, or the location of the application code, for a Managed Service for Apache Flink application.

Contents

S3ContentLocation

Information about the Amazon S3 bucket that contains the application code.

Type: S3ContentLocation object

Required: No

TextContent

The text-format code for a Managed Service for Apache Flink application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 102400.

Required: No

ZipFileContent

The zip-format code for a Managed Service for Apache Flink application.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 52428800.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

CodeContentDescription

Describes details about the code of a Managed Service for Apache Flink application.

Contents

CodeMD5

The checksum that can be used to validate zip-format code.

Type: String

Length Constraints: Fixed length of 128.

Required: No

CodeSize

The size in bytes of the application code. Can be used to validate zip-format code.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 52428800.

Required: No

S3ApplicationCodeLocationDescription

The S3 bucket Amazon Resource Name (ARN), file key, and object version of the application code stored in Amazon S3.

Type: S3ApplicationCodeLocationDescription object

Required: No

TextContent

The text-format code

Type: String

Length Constraints: Minimum length of 0. Maximum length of 102400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CodeContentUpdate

Describes an update to the code of an application. Not supported for Apache Zeppelin.

Contents

S3ContentLocationUpdate

Describes an update to the location of code for an application.

Type: S3ContentLocationUpdate object

Required: No

TextContentUpdate

Describes an update to the text code for an application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 102400.

Required: No

ZipFileContentUpdate

Describes an update to the zipped code for an application.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 52428800.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CSVMappingParameters

For a SQL-based Kinesis Data Analytics application, provides additional mapping information when the record format uses delimiters, such as CSV. For example, the following sample records use CSV format, where the records use the '*n*' as the row delimiter and a comma (",") as the column delimiter:

```
"name1", "address1"

"name2", "address2"
```

Contents

RecordColumnDelimiter

The column delimiter. For example, in a CSV format, a comma (",") is the typical column delimiter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

RecordRowDelimiter

The row delimiter. For example, in a CSV format, '*n*' is the typical row delimiter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

CustomArtifactConfiguration

Specifies dependency JARs, as well as JAR files that contain user-defined functions (UDF).

Contents

ArtifactType

UDF stands for user-defined functions. This type of artifact must be in an S3 bucket. A DEPENDENCY_JAR can be in either Maven or an S3 bucket.

Type: String

Valid Values: UDF | DEPENDENCY_JAR

Required: Yes

MavenReference

The parameters required to fully specify a Maven reference.

Type: MavenReference object

Required: No

S3ContentLocation

For a Managed Service for Apache Flink application provides a description of an Amazon S3 object, including the Amazon Resource Name (ARN) of the S3 bucket, the name of the Amazon S3 object that contains the data, and the version number of the Amazon S3 object that contains the data.

Type: S3ContentLocation object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

CustomArtifactConfigurationDescription

Specifies a dependency JAR or a JAR of user-defined functions.

Contents

ArtifactType

UDF stands for user-defined functions. This type of artifact must be in an S3 bucket. A DEPENDENCY_JAR can be in either Maven or an S3 bucket.

Type: String

Valid Values: UDF | DEPENDENCY_JAR

Required: No

MavenReferenceDescription

The parameters that are required to specify a Maven dependency.

Type: MavenReference object

Required: No

S3ContentLocationDescription

For a Managed Service for Apache Flink application provides a description of an Amazon S3 object, including the Amazon Resource Name (ARN) of the S3 bucket, the name of the Amazon S3 object that contains the data, and the version number of the Amazon S3 object that contains the data.

Type: S3ContentLocation object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

DeployAsApplicationConfiguration

The information required to deploy a Managed Service for Apache Flink Studio notebook as an application with durable state.

Contents

S3ContentLocation

The description of an Amazon S3 object that contains the Amazon Data Analytics application, including the Amazon Resource Name (ARN) of the S3 bucket, the name of the Amazon S3 object that contains the data, and the version number of the Amazon S3 object that contains the data.

Type: S3ContentBaseLocation object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DeployAsApplicationConfigurationDescription

The configuration information required to deploy an Amazon Data Analytics Studio notebook as an application with durable state.

Contents

S3ContentLocationDescription

The location that holds the data required to specify an Amazon Data Analytics application.

Type: S3ContentBaseLocationDescription object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DeployAsApplicationConfigurationUpdate

Updates to the configuration information required to deploy an Amazon Data Analytics Studio notebook as an application with durable state.

Contents

S3ContentLocationUpdate

Updates to the location that holds the data required to specify an Amazon Data Analytics application.

Type: S3ContentBaseLocationUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DestinationSchema

Describes the data format when records are written to the destination in a SQL-based Kinesis Data Analytics application.

Contents

RecordFormatType

Specifies the format of the records on the output stream.

Type: String

Valid Values: `JSON` | `CSV`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EnvironmentProperties

Describes execution properties for a Managed Service for Apache Flink application.

Contents

PropertyGroups

Describes the execution property groups.

Type: Array of PropertyGroup objects

Array Members: Maximum number of 50 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EnvironmentPropertyDescriptions

Describes the execution properties for an Apache Flink runtime.

Contents

PropertyGroupDescriptions

Describes the execution property groups.

Type: Array of PropertyGroup objects

Array Members: Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EnvironmentPropertyUpdates

Describes updates to the execution property groups for a Managed Service for Apache Flink application or a Studio notebook.

Contents

PropertyGroups

Describes updates to the execution property groups.

Type: Array of PropertyGroup objects

Array Members: Maximum number of 50 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ErrorInfo

A description of the error that caused an operation to fail.

Contents

ErrorString

An error message that is returned when an operation fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FlinkApplicationConfiguration

Describes configuration parameters for a Managed Service for Apache Flink application or a Studio notebook.

Contents

CheckpointConfiguration

Describes an application's checkpointing configuration. Checkpointing is the process of persisting application state for fault tolerance. For more information, see Checkpoints for Fault Tolerance in the Apache Flink Documentation.

Type: CheckpointConfiguration object

Required: No

MonitoringConfiguration

Describes configuration parameters for Amazon CloudWatch logging for an application.

Type: MonitoringConfiguration object

Required: No

ParallelismConfiguration

Describes parameters for how an application executes multiple tasks simultaneously.

Type: ParallelismConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FlinkApplicationConfigurationDescription

Describes configuration parameters for a Managed Service for Apache Flink application.

Contents

CheckpointConfigurationDescription

Describes an application's checkpointing configuration. Checkpointing is the process of persisting application state for fault tolerance.

Type: CheckpointConfigurationDescription object

Required: No

JobPlanDescription

The job plan for an application. For more information about the job plan, see Jobs and Scheduling in the Apache Flink Documentation. To retrieve the job plan for the application, use the DescribeApplication:IncludeAdditionalDetails parameter of the DescribeApplication operation.

Type: String

Required: No

MonitoringConfigurationDescription

Describes configuration parameters for Amazon CloudWatch logging for an application.

Type: MonitoringConfigurationDescription object

Required: No

ParallelismConfigurationDescription

Describes parameters for how an application executes multiple tasks simultaneously.

Type: ParallelismConfigurationDescription object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

FlinkApplicationConfigurationUpdate

Describes updates to the configuration parameters for a Managed Service for Apache Flink application.

Contents

CheckpointConfigurationUpdate

Describes updates to an application's checkpointing configuration. Checkpointing is the process of persisting application state for fault tolerance.

Type: CheckpointConfigurationUpdate object

Required: No

MonitoringConfigurationUpdate

Describes updates to the configuration parameters for Amazon CloudWatch logging for an application.

Type: MonitoringConfigurationUpdate object

Required: No

ParallelismConfigurationUpdate

Describes updates to the parameters for how an application executes multiple tasks simultaneously.

Type: ParallelismConfigurationUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

FlinkRunConfiguration

Describes the starting parameters for a Managed Service for Apache Flink application.

Contents

AllowNonRestoredState

When restoring from a snapshot, specifies whether the runtime is allowed to skip a state that cannot be mapped to the new program. This will happen if the program is updated between snapshots to remove stateful parameters, and state data in the snapshot no longer corresponds to valid application data. For more information, see Allowing Non-Restored State in the Apache Flink documentation.

> **Note**
>
> This value defaults to `false`. If you update your application without specifying this parameter, `AllowNonRestoredState` will be set to `false`, even if it was previously set to `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

GlueDataCatalogConfiguration

The configuration of the Glue Data Catalog that you use for Apache Flink SQL queries and table API transforms that you write in an application.

Contents

DatabaseARN

The Amazon Resource Name (ARN) of the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

GlueDataCatalogConfigurationDescription

The configuration of the Glue Data Catalog that you use for Apache Flink SQL queries and table API transforms that you write in an application.

Contents

DatabaseARN

The Amazon Resource Name (ARN) of the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

GlueDataCatalogConfigurationUpdate

Updates to the configuration of the Glue Data Catalog that you use for SQL queries that you write in a Managed Service for Apache Flink Studio notebook.

Contents

DatabaseARNUpdate

The updated Amazon Resource Name (ARN) of the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Input

When you configure the application input for a SQL-based Kinesis Data Analytics application, you specify the streaming source, the in-application stream name that is created, and the mapping between the two.

Contents

InputSchema

Describes the format of the data in the streaming source, and how each data element maps to corresponding columns in the in-application stream that is being created.

Also used to describe the format of the reference data source.

Type: SourceSchema object

Required: Yes

NamePrefix

The name prefix to use when creating an in-application stream. Suppose that you specify a prefix "`MyInApplicationStream`." Kinesis Data Analytics then creates one or more (as per the `InputParallelism` count you specified) in-application streams with the names "`MyInApplicationStream_001`," "`MyInApplicationStream_002`," and so on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: Yes

InputParallelism

Describes the number of in-application streams to create.

Type: InputParallelism object

Required: No

InputProcessingConfiguration

The InputProcessingConfiguration for the input. An input processor transforms records as they are received from the stream, before the application's SQL code executes. Currently, the only input processing configuration available is InputLambdaProcessor.

Type: InputProcessingConfiguration object

Required: No

KinesisFirehoseInput

If the streaming source is an Amazon Kinesis Data Firehose delivery stream, identifies the delivery stream's ARN.

Type: KinesisFirehoseInput object

Required: No

KinesisStreamsInput

If the streaming source is an Amazon Kinesis data stream, identifies the stream's Amazon Resource Name (ARN).

Type: KinesisStreamsInput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputDescription

Describes the application input configuration for a SQL-based Kinesis Data Analytics application.

Contents

InAppStreamNames

Returns the in-application stream names that are mapped to the stream source.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: No

InputId

The input ID that is associated with the application input. This is the ID that Kinesis Data Analytics assigns to each input configuration that you add to your application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

InputParallelism

Describes the configured parallelism (number of in-application streams mapped to the streaming source).

Type: InputParallelism object

Required: No

InputProcessingConfigurationDescription

The description of the preprocessor that executes on records in this input before the application's code is run.

Type: InputProcessingConfigurationDescription object

Required: No

InputSchema

Describes the format of the data in the streaming source, and how each data element maps to corresponding columns in the in-application stream that is being created.

Type: SourceSchema object

Required: No

InputStartingPositionConfiguration

The point at which the application is configured to read from the input stream.

Type: InputStartingPositionConfiguration object

Required: No

KinesisFirehoseInputDescription

If a Kinesis Data Firehose delivery stream is configured as a streaming source, provides the delivery stream's ARN.

Type: KinesisFirehoseInputDescription object

Required: No

KinesisStreamsInputDescription

If a Kinesis data stream is configured as a streaming source, provides the Kinesis data stream's Amazon Resource Name (ARN).

Type: KinesisStreamsInputDescription object

Required: No

NamePrefix

The in-application name prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputLambdaProcessor

An object that contains the Amazon Resource Name (ARN) of the Amazon Lambda function that is used to preprocess records in the stream in a SQL-based Kinesis Data Analytics application.

Contents

ResourceARN

The ARN of the Amazon Lambda function that operates on records in the stream.

> **Note**
>
> To specify an earlier version of the Lambda function than the latest, include the Lambda function version in the Lambda function ARN. For more information about Lambda ARNs, see Example ARNs: Amazon Lambda

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputLambdaProcessorDescription

For a SQL-based Kinesis Data Analytics application, an object that contains the Amazon Resource Name (ARN) of the Amazon Lambda function that is used to preprocess records in the stream.

Contents

ResourceARN

The ARN of the Amazon Lambda function that is used to preprocess the records in the stream.

> **Note**
>
> To specify an earlier version of the Lambda function than the latest, include the Lambda function version in the Lambda function ARN. For more information about Lambda ARNs, see Example ARNs: Amazon Lambda

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that is used to access the Amazon Lambda function.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputLambdaProcessorUpdate

For a SQL-based Kinesis Data Analytics application, represents an update to the InputLambdaProcessor that is used to preprocess the records in the stream.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the new Amazon Lambda function that is used to preprocess the records in the stream.

> **Note**
>
> To specify an earlier version of the Lambda function than the latest, include the Lambda function version in the Lambda function ARN. For more information about Lambda ARNs, see Example ARNs: Amazon Lambda

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputParallelism

For a SQL-based Kinesis Data Analytics application, describes the number of in-application streams to create for a given streaming source.

Contents

Count

The number of in-application streams to create.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputParallelismUpdate

For a SQL-based Kinesis Data Analytics application, provides updates to the parallelism count.

Contents

CountUpdate

The number of in-application streams to create for the specified streaming source.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputProcessingConfiguration

For a SQL-based Kinesis Data Analytics application, describes a processor that is used to preprocess the records in the stream before being processed by your application code. Currently, the only input processor available is Amazon Lambda.

Contents

InputLambdaProcessor

The InputLambdaProcessor that is used to preprocess the records in the stream before being processed by your application code.

Type: InputLambdaProcessor object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputProcessingConfigurationDescription

For a SQL-based Kinesis Data Analytics application, provides the configuration information about an input processor. Currently, the only input processor available is Amazon Lambda.

Contents

InputLambdaProcessorDescription

Provides configuration information about the associated InputLambdaProcessorDescription

Type: InputLambdaProcessorDescription object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputProcessingConfigurationUpdate

For a SQL-based Kinesis Data Analytics application, describes updates to an InputProcessingConfiguration.

Contents

InputLambdaProcessorUpdate

Provides update information for an InputLambdaProcessor.

Type: InputLambdaProcessorUpdate object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputSchemaUpdate

Describes updates for an SQL-based Kinesis Data Analytics application's input schema.

Contents

RecordColumnUpdates

A list of `RecordColumn` objects. Each object describes the mapping of the streaming source element to the corresponding column in the in-application stream.

Type: Array of RecordColumn objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

RecordEncodingUpdate

Specifies the encoding of the records in the streaming source; for example, UTF-8.

Type: String

Length Constraints: Fixed length of 5.

Pattern: `UTF-8`

Required: No

RecordFormatUpdate

Specifies the format of the records on the streaming source.

Type: RecordFormat object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputStartingPositionConfiguration

Describes the point at which the application reads from the streaming source.

Contents

InputStartingPosition

The starting position on the stream.

- `NOW` - Start reading just after the most recent record in the stream, and start at the request timestamp that the customer issued.
- `TRIM_HORIZON` - Start reading at the last untrimmed record in the stream, which is the oldest record available in the stream. This option is not available for an Amazon Kinesis Data Firehose delivery stream.
- `LAST_STOPPED_POINT` - Resume reading from where the application last stopped reading.

Type: String

Valid Values: `NOW | TRIM_HORIZON | LAST_STOPPED_POINT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputUpdate

For a SQL-based Kinesis Data Analytics application, describes updates to a specific input configuration (identified by the `InputId` of an application).

Contents

InputId

The input ID of the application input to be updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

InputParallelismUpdate

Describes the parallelism updates (the number of in-application streams Kinesis Data Analytics creates for the specific streaming source).

Type: InputParallelismUpdate object

Required: No

InputProcessingConfigurationUpdate

Describes updates to an InputProcessingConfiguration.

Type: InputProcessingConfigurationUpdate object

Required: No

InputSchemaUpdate

Describes the data format on the streaming source, and how record elements on the streaming source map to columns of the in-application stream that is created.

Type: InputSchemaUpdate object

Required: No

KinesisFirehoseInputUpdate

If a Kinesis Data Firehose delivery stream is the streaming source to be updated, provides an updated stream ARN.

Type: KinesisFirehoseInputUpdate object

Required: No

KinesisStreamsInputUpdate

If a Kinesis data stream is the streaming source to be updated, provides an updated stream Amazon Resource Name (ARN).

Type: KinesisStreamsInputUpdate object

Required: No

NamePrefixUpdate

The name prefix for in-application streams that Kinesis Data Analytics creates for the specific streaming source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

JSONMappingParameters

For a SQL-based Kinesis Data Analytics application, provides additional mapping information when JSON is the record format on the streaming source.

Contents

RecordRowPath

The path to the top-level parent that contains the records.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: `^(?=^\$)(?=^\S+$).*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseInput

For a SQL-based Kinesis Data Analytics application, identifies a Kinesis Data Firehose delivery stream as the streaming source. You provide the delivery stream's Amazon Resource Name (ARN).

Contents

ResourceARN

The Amazon Resource Name (ARN) of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseInputDescription

Describes the Amazon Kinesis Data Firehose delivery stream that is configured as the streaming source in the application input configuration.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that Kinesis Data Analytics assumes to access the stream.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseInputUpdate

For a SQL-based Kinesis Data Analytics application, when updating application input configuration, provides information about a Kinesis Data Firehose delivery stream as the streaming source.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the input delivery stream to read.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseOutput

For a SQL-based Kinesis Data Analytics application, when configuring application output, identifies a Kinesis Data Firehose delivery stream as the destination. You provide the stream Amazon Resource Name (ARN) of the delivery stream.

Contents

ResourceARN

The ARN of the destination delivery stream to write to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseOutputDescription

For a SQL-based Kinesis Data Analytics application's output, describes the Kinesis Data Firehose delivery stream that is configured as its destination.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that Kinesis Data Analytics can assume to access the stream.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisFirehoseOutputUpdate

For a SQL-based Kinesis Data Analytics application, when updating an output configuration using the UpdateApplication operation, provides information about a Kinesis Data Firehose delivery stream that is configured as the destination.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the delivery stream to write to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsInput

Identifies a Kinesis data stream as the streaming source. You provide the stream's Amazon Resource Name (ARN).

Contents

ResourceARN

The ARN of the input Kinesis data stream to read.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsInputDescription

For a SQL-based Kinesis Data Analytics application, describes the Kinesis data stream that is configured as the streaming source in the application input configuration.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the Kinesis data stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that Kinesis Data Analytics can assume to access the stream.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsInputUpdate

When you update the input configuration for a SQL-based Kinesis Data Analytics application, provides information about a Kinesis stream as the streaming source.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the input Kinesis data stream to read.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsOutput

When you configure a SQL-based Kinesis Data Analytics application's output, identifies a Kinesis data stream as the destination. You provide the stream Amazon Resource Name (ARN).

Contents

ResourceARN

The ARN of the destination Kinesis data stream to write to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsOutputDescription

For an SQL-based Kinesis Data Analytics application's output, describes the Kinesis data stream that is configured as its destination.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the Kinesis data stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that Kinesis Data Analytics can assume to access the stream.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

KinesisStreamsOutputUpdate

When you update a SQL-based Kinesis Data Analytics application's output configuration using the UpdateApplication operation, provides information about a Kinesis data stream that is configured as the destination.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the Kinesis data stream where you want to write the output.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

LambdaOutput

When you configure a SQL-based Kinesis Data Analytics application's output, identifies an Amazon Lambda function as the destination. You provide the function Amazon Resource Name (ARN) of the Lambda function.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the destination Lambda function to write to.

> **Note**
>
> To specify an earlier version of the Lambda function than the latest, include the Lambda function version in the Lambda function ARN. For more information about Lambda ARNs, see Example ARNs: Amazon Lambda

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

LambdaOutputDescription

For a SQL-based Kinesis Data Analytics application's output, describes the Amazon Lambda function that is configured as its destination.

Contents

ResourceARN

The Amazon Resource Name (ARN) of the destination Lambda function.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the IAM role that Kinesis Data Analytics can assume to write to the destination function.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

LambdaOutputUpdate

When you update an SQL-based Kinesis Data Analytics application's output configuration using the UpdateApplication operation, provides information about an Amazon Lambda function that is configured as the destination.

Contents

ResourceARNUpdate

The Amazon Resource Name (ARN) of the destination Amazon Lambda function.

> **Note**
>
> To specify an earlier version of the Lambda function than the latest, include the Lambda function version in the Lambda function ARN. For more information about Lambda ARNs, see Example ARNs: Amazon Lambda

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MappingParameters

When you configure a SQL-based Kinesis Data Analytics application's input at the time of creating or updating an application, provides additional mapping information specific to the record format (such as JSON, CSV, or record fields delimited by some delimiter) on the streaming source.

Contents

CSVMappingParameters

Provides additional mapping information when the record format uses delimiters (for example, CSV).

Type: CSVMappingParameters object

Required: No

JSONMappingParameters

Provides additional mapping information when JSON is the record format on the streaming source.

Type: JSONMappingParameters object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MavenReference

The information required to specify a Maven reference. You can use Maven references to specify dependency JAR files.

Contents

ArtifactId

The artifact ID of the Maven reference.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

GroupId

The group ID of the Maven reference.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Version

The version of the Maven reference.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MonitoringConfiguration

Describes configuration parameters for Amazon CloudWatch logging for an application. For more information about CloudWatch logging, see Monitoring.

Contents

ConfigurationType

Describes whether to use the default CloudWatch logging configuration for an application. You must set this property to `CUSTOM` in order to set the `LogLevel` or `MetricsLevel` parameters.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: Yes

LogLevel

Describes the verbosity of the CloudWatch Logs for an application.

Type: String

Valid Values: `INFO | WARN | ERROR | DEBUG`

Required: No

MetricsLevel

Describes the granularity of the CloudWatch Logs for an application. The `Parallelism` level is not recommended for applications with a Parallelism over 64 due to excessive costs.

Type: String

Valid Values: `APPLICATION | TASK | OPERATOR | PARALLELISM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MonitoringConfigurationDescription

Describes configuration parameters for CloudWatch logging for an application.

Contents

ConfigurationType

Describes whether to use the default CloudWatch logging configuration for an application.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

LogLevel

Describes the verbosity of the CloudWatch Logs for an application.

Type: String

Valid Values: `INFO | WARN | ERROR | DEBUG`

Required: No

MetricsLevel

Describes the granularity of the CloudWatch Logs for an application.

Type: String

Valid Values: `APPLICATION | TASK | OPERATOR | PARALLELISM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

MonitoringConfigurationUpdate

Describes updates to configuration parameters for Amazon CloudWatch logging for an application.

Contents

ConfigurationTypeUpdate

Describes updates to whether to use the default CloudWatch logging configuration for an application. You must set this property to `CUSTOM` in order to set the `LogLevel` or `MetricsLevel` parameters.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

LogLevelUpdate

Describes updates to the verbosity of the CloudWatch Logs for an application.

Type: String

Valid Values: `INFO | WARN | ERROR | DEBUG`

Required: No

MetricsLevelUpdate

Describes updates to the granularity of the CloudWatch Logs for an application. The `Parallelism` level is not recommended for applications with a Parallelism over 64 due to excessive costs.

Type: String

Valid Values: `APPLICATION | TASK | OPERATOR | PARALLELISM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OperationFailureDetails

Provides a description of the operation failure.

Contents

ErrorInfo

A description of the error that caused an operation to fail.

Type: ErrorInfo object

Required: No

RollbackOperationId

The rollback operation ID of the system-rollback operation that executed due to failure in the current operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Output

Describes a SQL-based Kinesis Data Analytics application's output configuration, in which you identify an in-application stream and a destination where you want the in-application stream data to be written. The destination can be a Kinesis data stream or a Kinesis Data Firehose delivery stream.

Contents

DestinationSchema

Describes the data format when records are written to the destination.

Type: DestinationSchema object

Required: Yes

Name

The name of the in-application stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: Yes

KinesisFirehoseOutput

Identifies a Kinesis Data Firehose delivery stream as the destination.

Type: KinesisFirehoseOutput object

Required: No

KinesisStreamsOutput

Identifies a Kinesis data stream as the destination.

Type: KinesisStreamsOutput object

Required: No

LambdaOutput

Identifies an Amazon Lambda function as the destination.

Type: LambdaOutput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OutputDescription

For a SQL-based Kinesis Data Analytics application, describes the application output configuration, which includes the in-application stream name and the destination where the stream data is written. The destination can be a Kinesis data stream or a Kinesis Data Firehose delivery stream.

Contents

DestinationSchema

The data format used for writing data to the destination.

Type: DestinationSchema object

Required: No

KinesisFirehoseOutputDescription

Describes the Kinesis Data Firehose delivery stream that is configured as the destination where output is written.

Type: KinesisFirehoseOutputDescription object

Required: No

KinesisStreamsOutputDescription

Describes the Kinesis data stream that is configured as the destination where output is written.

Type: KinesisStreamsOutputDescription object

Required: No

LambdaOutputDescription

Describes the Lambda function that is configured as the destination where output is written.

Type: LambdaOutputDescription object

Required: No

Name

The name of the in-application stream that is configured as output.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: No

OutputId

A unique identifier for the output configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OutputUpdate

For a SQL-based Kinesis Data Analytics application, describes updates to the output configuration identified by the `OutputId`.

Contents

OutputId

Identifies the specific output configuration that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

DestinationSchemaUpdate

Describes the data format when records are written to the destination.

Type: DestinationSchema object

Required: No

KinesisFirehoseOutputUpdate

Describes a Kinesis Data Firehose delivery stream as the destination for the output.

Type: KinesisFirehoseOutputUpdate object

Required: No

KinesisStreamsOutputUpdate

Describes a Kinesis data stream as the destination for the output.

Type: KinesisStreamsOutputUpdate object

Required: No

LambdaOutputUpdate

Describes an Amazon Lambda function as the destination for the output.

Type: LambdaOutputUpdate object

Required: No

NameUpdate

If you want to specify a different in-application stream for this output configuration, use this field to specify the new in-application stream name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[^-\s<>&]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParallelismConfiguration

Describes parameters for how a Managed Service for Apache Flink application executes multiple tasks simultaneously. For more information about parallelism, see Parallel Execution in the Apache Flink Documentation.

Contents

ConfigurationType

Describes whether the application uses the default parallelism for the Managed Service for Apache Flink service. You must set this property to `CUSTOM` in order to change your application's `AutoScalingEnabled`, `Parallelism`, or `ParallelismPerKPU` properties.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: Yes

AutoScalingEnabled

Describes whether the Managed Service for Apache Flink service can increase the parallelism of the application in response to increased throughput.

Type: Boolean

Required: No

Parallelism

Describes the initial number of parallel tasks that a Managed Service for Apache Flink application can perform. If `AutoScalingEnabled` is set to True, Managed Service for Apache Flink increases the `CurrentParallelism` value in response to application load. The service can increase the `CurrentParallelism` value up to the maximum parallelism, which is `ParallelismPerKPU` times the maximum KPUs for the application. The maximum KPUs for an application is 64 by default, and can be increased by requesting a limit increase. If application load is reduced, the service can reduce the `CurrentParallelism` value down to the `Parallelism` setting.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

ParallelismPerKPU

Describes the number of parallel tasks that a Managed Service for Apache Flink application can perform per Kinesis Processing Unit (KPU) used by the application. For more information about KPUs, see Amazon Managed Service for Apache Flink Pricing.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParallelismConfigurationDescription

Describes parameters for how a Managed Service for Apache Flink application executes multiple tasks simultaneously.

Contents

AutoScalingEnabled

Describes whether the Managed Service for Apache Flink service can increase the parallelism of the application in response to increased throughput.

Type: Boolean

Required: No

ConfigurationType

Describes whether the application uses the default parallelism for the Managed Service for Apache Flink service.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

CurrentParallelism

Describes the current number of parallel tasks that a Managed Service for Apache Flink application can perform. If `AutoScalingEnabled` is set to True, Managed Service for Apache Flink can increase this value in response to application load. The service can increase this value up to the maximum parallelism, which is `ParallelismPerKPU` times the maximum KPUs for the application. The maximum KPUs for an application is 32 by default, and can be increased by requesting a limit increase. If application load is reduced, the service can reduce the `CurrentParallelism` value down to the `Parallelism` setting.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

Parallelism

Describes the initial number of parallel tasks that a Managed Service for Apache Flink application can perform. If `AutoScalingEnabled` is set to True, then Managed Service for Apache Flink can increase the `CurrentParallelism` value in response to application load. The service can increase `CurrentParallelism` up to the maximum parallelism, which is `ParalellismPerKPU` times the maximum KPUs for the application. The maximum KPUs for an application is 64 by default, and can be increased by requesting a limit increase. If application load is reduced, the service can reduce the `CurrentParallelism` value down to the `Parallelism` setting.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

ParallelismPerKPU

Describes the number of parallel tasks that a Managed Service for Apache Flink application can perform per Kinesis Processing Unit (KPU) used by the application.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParallelismConfigurationUpdate

Describes updates to parameters for how an application executes multiple tasks simultaneously.

Contents

AutoScalingEnabledUpdate

Describes updates to whether the Managed Service for Apache Flink service can increase the parallelism of a Managed Service for Apache Flink application in response to increased throughput.

Type: Boolean

Required: No

ConfigurationTypeUpdate

Describes updates to whether the application uses the default parallelism for the Managed Service for Apache Flink service, or if a custom parallelism is used. You must set this property to `CUSTOM` in order to change your application's `AutoScalingEnabled`, `Parallelism`, or `ParallelismPerKPU` properties.

Type: String

Valid Values: `DEFAULT | CUSTOM`

Required: No

ParallelismPerKPUUpdate

Describes updates to the number of parallel tasks an application can perform per Kinesis Processing Unit (KPU) used by the application.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

ParallelismUpdate

Describes updates to the initial number of parallel tasks an application can perform. If `AutoScalingEnabled` is set to True, then Managed Service for Apache Flink can increase

the `CurrentParallelism` value in response to application load. The service can increase `CurrentParallelism` up to the maximum parallelism, which is `ParalellismPerKPU` times the maximum KPUs for the application. The maximum KPUs for an application is 32 by default, and can be increased by requesting a limit increase. If application load is reduced, the service will reduce `CurrentParallelism` down to the `Parallelism` setting.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PropertyGroup

Property key-value pairs passed into an application.

Contents

PropertyGroupId

Describes the key of an application execution property key-value pair.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

PropertyMap

Describes the value of an application execution property key-value pair.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 2048.

Value Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RecordColumn

For a SQL-based Kinesis Data Analytics application, describes the mapping of each data element in the streaming source to the corresponding column in the in-application stream.

Also used to describe the format of the reference data source.

Contents

Name

The name of the column that is created in the in-application input stream or reference table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^-\s<>&]*`

Required: Yes

SqlType

The type of column created in the in-application input stream or reference table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Mapping

A reference to the data element in the streaming input or the reference data source.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RecordFormat

For a SQL-based Kinesis Data Analytics application, describes the record format and relevant mapping information that should be applied to schematize the records on the stream.

Contents

RecordFormatType

The type of record format.

Type: String

Valid Values: `JSON | CSV`

Required: Yes

MappingParameters

When you configure application input at the time of creating or updating an application, provides additional mapping information specific to the record format (such as JSON, CSV, or record fields delimited by some delimiter) on the streaming source.

Type: MappingParameters object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ReferenceDataSource

For a SQL-based Kinesis Data Analytics application, describes the reference data source by providing the source information (Amazon S3 bucket name and object key name), the resulting in-application table name that is created, and the necessary schema to map the data elements in the Amazon S3 object to the in-application table.

Contents

ReferenceSchema

Describes the format of the data in the streaming source, and how each data element maps to corresponding columns created in the in-application stream.

Type: SourceSchema object

Required: Yes

TableName

The name of the in-application table to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

S3ReferenceDataSource

Identifies the S3 bucket and object that contains the reference data. A SQL-based Kinesis Data Analytics application loads reference data only once. If the data changes, you call the UpdateApplication operation to trigger reloading of data into your application.

Type: S3ReferenceDataSource object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ReferenceDataSourceDescription

For a SQL-based Kinesis Data Analytics application, describes the reference data source configured for an application.

Contents

ReferenceId

The ID of the reference data source. This is the ID that Kinesis Data Analytics assigns when you add the reference data source to your application using the CreateApplication or UpdateApplication operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

S3ReferenceDataSourceDescription

Provides the Amazon S3 bucket name, the object key name that contains the reference data.

Type: S3ReferenceDataSourceDescription object

Required: Yes

TableName

The in-application table name created by the specific reference data source configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

ReferenceSchema

Describes the format of the data in the streaming source, and how each data element maps to corresponding columns created in the in-application stream.

Type: SourceSchema object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ReferenceDataSourceUpdate

When you update a reference data source configuration for a SQL-based Kinesis Data Analytics application, this object provides all the updated values (such as the source bucket name and object key name), the in-application table name that is created, and updated mapping information that maps the data in the Amazon S3 object to the in-application reference table that is created.

Contents

ReferenceId

The ID of the reference data source that is being updated. You can use the DescribeApplication operation to get this value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

ReferenceSchemaUpdate

Describes the format of the data in the streaming source, and how each data element maps to corresponding columns created in the in-application stream.

Type: SourceSchema object

Required: No

S3ReferenceDataSourceUpdate

Describes the S3 bucket name, object key name, and IAM role that Kinesis Data Analytics can assume to read the Amazon S3 object on your behalf and populate the in-application reference table.

Type: S3ReferenceDataSourceUpdate object

Required: No

TableNameUpdate

The in-application table name that is created by this update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RunConfiguration

Describes the starting parameters for an Managed Service for Apache Flink application.

Contents

ApplicationRestoreConfiguration

Describes the restore behavior of a restarting application.

Type: ApplicationRestoreConfiguration object

Required: No

FlinkRunConfiguration

Describes the starting parameters for a Managed Service for Apache Flink application.

Type: FlinkRunConfiguration object

Required: No

SqlRunConfigurations

Describes the starting parameters for a SQL-based Kinesis Data Analytics application application.

Type: Array of SqlRunConfiguration objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RunConfigurationDescription

Describes the starting properties for a Managed Service for Apache Flink application.

Contents

ApplicationRestoreConfigurationDescription

Describes the restore behavior of a restarting application.

Type: ApplicationRestoreConfiguration object

Required: No

FlinkRunConfigurationDescription

Describes the starting parameters for a Managed Service for Apache Flink application.

Type: FlinkRunConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

RunConfigurationUpdate

Describes the updates to the starting parameters for a Managed Service for Apache Flink application.

Contents

ApplicationRestoreConfiguration

Describes updates to the restore behavior of a restarting application.

Type: ApplicationRestoreConfiguration object

Required: No

FlinkRunConfiguration

Describes the starting parameters for a Managed Service for Apache Flink application.

Type: FlinkRunConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ApplicationCodeLocationDescription

Describes the location of an application's code stored in an S3 bucket.

Contents

BucketARN

The Amazon Resource Name (ARN) for the S3 bucket containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

FileKey

The file key for the object containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

ObjectVersion

The version of the object containing the application code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3Configuration

For a SQL-based Kinesis Data Analytics application, provides a description of an Amazon S3 data source, including the Amazon Resource Name (ARN) of the S3 bucket and the name of the Amazon S3 object that contains the data.

Contents

BucketARN

The ARN of the S3 bucket that contains the data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

FileKey

The name of the object that contains the data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ContentBaseLocation

The S3 bucket that holds the application information.

Contents

BucketARN

The Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

BasePath

The base path for the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9/!-_.*'()]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ContentBaseLocationDescription

The description of the S3 base location that holds the application.

Contents

BucketARN

The Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

BasePath

The base path for the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9/!-_.*'()]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ContentBaseLocationUpdate

The information required to update the S3 base location that holds the application.

Contents

BasePathUpdate

The updated S3 bucket path.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9/!-_.*'()]+`

Required: No

BucketARNUpdate

The updated Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ContentLocation

For a Managed Service for Apache Flink application provides a description of an Amazon S3 object, including the Amazon Resource Name (ARN) of the S3 bucket, the name of the Amazon S3 object that contains the data, and the version number of the Amazon S3 object that contains the data.

Contents

BucketARN

The Amazon Resource Name (ARN) for the S3 bucket containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

FileKey

The file key for the object containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

ObjectVersion

The version of the object containing the application code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ContentLocationUpdate

Describes an update for the Amazon S3 code content location for an application.

Contents

BucketARNUpdate

The new Amazon Resource Name (ARN) for the S3 bucket containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

FileKeyUpdate

The new file key for the object containing the application code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

ObjectVersionUpdate

The new version of the object containing the application code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ReferenceDataSource

For a SQL-based Kinesis Data Analytics application, identifies the Amazon S3 bucket and object that contains the reference data.

A SQL-based Kinesis Data Analytics application loads reference data only once. If the data changes, you call the UpdateApplication operation to trigger reloading of data into your application.

Contents

BucketARN

The Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

FileKey

The object key name containing the reference data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ReferenceDataSourceDescription

For a SQL-based Kinesis Data Analytics application, provides the bucket name and object key name that stores the reference data.

Contents

BucketARN

The Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

FileKey

Amazon S3 object key name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

ReferenceRoleARN

The ARN of the IAM role that Kinesis Data Analytics can assume to read the Amazon S3 object on your behalf to populate the in-application reference table.

> **Note**
>
> Provided for backward compatibility. Applications that are created with the current API version have an application-level service execution role rather than a resource-level role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3ReferenceDataSourceUpdate

For a SQL-based Kinesis Data Analytics application, describes the Amazon S3 bucket name and object key name for an in-application reference table.

Contents

BucketARNUpdate

The Amazon Resource Name (ARN) of the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: No

FileKeyUpdate

The object key name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SnapshotDetails

Provides details about a snapshot of application state.

Contents

ApplicationVersionId

The current application version ID when the snapshot was created.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 999999999.

Required: Yes

SnapshotName

The identifier for the application snapshot.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SnapshotStatus

The status of the application snapshot.

Type: String

Valid Values: `CREATING | READY | DELETING | FAILED`

Required: Yes

ApplicationEncryptionConfigurationDescription

Specifies the encryption settings of data at rest for the application snapshot.

Type: ApplicationEncryptionConfigurationDescription object

Required: No

RuntimeEnvironment

The Flink Runtime for the application snapshot.

Type: String

Valid Values: `SQL-1_0 | FLINK-1_6 | FLINK-1_8 | ZEPPELIN-FLINK-1_0 | FLINK-1_11 | FLINK-1_13 | ZEPPELIN-FLINK-2_0 | FLINK-1_15 | ZEPPELIN-FLINK-3_0 | FLINK-1_18 | FLINK-1_19 | FLINK-1_20`

Required: No

SnapshotCreationTimestamp

The timestamp of the application snapshot.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SourceSchema

For a SQL-based Kinesis Data Analytics application, describes the format of the data in the streaming source, and how each data element maps to corresponding columns created in the in-application stream.

Contents

RecordColumns

A list of `RecordColumn` objects.

Type: Array of RecordColumn objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: Yes

RecordFormat

Specifies the format of the records on the streaming source.

Type: RecordFormat object

Required: Yes

RecordEncoding

Specifies the encoding of the records in the streaming source. For example, UTF-8.

Type: String

Length Constraints: Fixed length of 5.

Pattern: `UTF-8`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SqlApplicationConfiguration

Describes the inputs, outputs, and reference data sources for a SQL-based Kinesis Data Analytics application.

Contents

Inputs

The array of Input objects describing the input streams used by the application.

Type: Array of Input objects

Required: No

Outputs

The array of Output objects describing the destination streams used by the application.

Type: Array of Output objects

Required: No

ReferenceDataSources

The array of ReferenceDataSource objects describing the reference data sources used by the application.

Type: Array of ReferenceDataSource objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SqlApplicationConfigurationDescription

Describes the inputs, outputs, and reference data sources for a SQL-based Kinesis Data Analytics application.

Contents

InputDescriptions

The array of InputDescription objects describing the input streams used by the application.

Type: Array of InputDescription objects

Required: No

OutputDescriptions

The array of OutputDescription objects describing the destination streams used by the application.

Type: Array of OutputDescription objects

Required: No

ReferenceDataSourceDescriptions

The array of ReferenceDataSourceDescription objects describing the reference data sources used by the application.

Type: Array of ReferenceDataSourceDescription objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SqlApplicationConfigurationUpdate

Describes updates to the input streams, destination streams, and reference data sources for a SQL-based Kinesis Data Analytics application.

Contents

InputUpdates

The array of InputUpdate objects describing the new input streams used by the application.

Type: Array of InputUpdate objects

Required: No

OutputUpdates

The array of OutputUpdate objects describing the new destination streams used by the application.

Type: Array of OutputUpdate objects

Required: No

ReferenceDataSourceUpdates

The array of ReferenceDataSourceUpdate objects describing the new reference data sources used by the application.

Type: Array of ReferenceDataSourceUpdate objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SqlRunConfiguration

Describes the starting parameters for a SQL-based Kinesis Data Analytics application.

Contents

InputId

The input source ID. You can get this ID by calling the DescribeApplication operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

InputStartingPositionConfiguration

The point at which you want the application to start processing records from the streaming source.

Type: InputStartingPositionConfiguration object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Tag

A key-value pair (the value is optional) that you can define and assign to Amazon resources. If you specify a tag that already exists, the tag value is replaced with the value that you specify in the request. Note that the maximum number of application tags includes system tags. The maximum number of user-defined application tags is 50. For more information, see Using Tagging.

Contents

Key

The key of the key-value tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The value of the key-value tag. The value is optional.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

VpcConfiguration

Describes the parameters of a VPC used by the application.

Contents

SecurityGroupIds

The array of SecurityGroup IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

SubnetIds

The array of Subnet IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 16 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

VpcConfigurationDescription

Describes the parameters of a VPC used by the application.

Contents

SecurityGroupIds

The array of SecurityGroup IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

SubnetIds

The array of Subnet IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 16 items.

Required: Yes

VpcConfigurationId

The ID of the VPC configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

VpcId

The ID of the associated VPC.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

VpcConfigurationUpdate

Describes updates to the VPC configuration used by the application.

Contents

VpcConfigurationId

Describes an update to the ID of the VPC configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

SecurityGroupIdUpdates

Describes updates to the array of SecurityGroup IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

SubnetIdUpdates

Describes updates to the array of Subnet IDs used by the VPC configuration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 16 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinApplicationConfiguration

The configuration of a Managed Service for Apache Flink Studio notebook.

Contents

CatalogConfiguration

The Amazon Glue Data Catalog that you use in queries in a Managed Service for Apache Flink Studio notebook.

Type: CatalogConfiguration object

Required: No

CustomArtifactsConfiguration

Custom artifacts are dependency JARs and user-defined functions (UDF).

Type: Array of CustomArtifactConfiguration objects

Array Members: Maximum number of 50 items.

Required: No

DeployAsApplicationConfiguration

The information required to deploy a Managed Service for Apache Flink Studio notebook as an application with durable state.

Type: DeployAsApplicationConfiguration object

Required: No

MonitoringConfiguration

The monitoring configuration of a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinMonitoringConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinApplicationConfigurationDescription

The configuration of a Managed Service for Apache Flink Studio notebook.

Contents

MonitoringConfigurationDescription

The monitoring configuration of a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinMonitoringConfigurationDescription object

Required: Yes

CatalogConfigurationDescription

The Amazon Glue Data Catalog that is associated with the Managed Service for Apache Flink Studio notebook.

Type: CatalogConfigurationDescription object

Required: No

CustomArtifactsConfigurationDescription

Custom artifacts are dependency JARs and user-defined functions (UDF).

Type: Array of CustomArtifactConfigurationDescription objects

Array Members: Maximum number of 50 items.

Required: No

DeployAsApplicationConfigurationDescription

The parameters required to deploy a Managed Service for Apache Flink Studio notebook as an application with durable state.

Type: DeployAsApplicationConfigurationDescription object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinApplicationConfigurationUpdate

Updates to the configuration of Managed Service for Apache Flink Studio notebook.

Contents

CatalogConfigurationUpdate

Updates to the configuration of the Amazon Glue Data Catalog that is associated with the Managed Service for Apache Flink Studio notebook.

Type: CatalogConfigurationUpdate object

Required: No

CustomArtifactsConfigurationUpdate

Updates to the customer artifacts. Custom artifacts are dependency JAR files and user-defined functions (UDF).

Type: Array of CustomArtifactConfiguration objects

Array Members: Maximum number of 50 items.

Required: No

DeployAsApplicationConfigurationUpdate

Type: DeployAsApplicationConfigurationUpdate object

Required: No

MonitoringConfigurationUpdate

Updates to the monitoring configuration of a Managed Service for Apache Flink Studio notebook.

Type: ZeppelinMonitoringConfigurationUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinMonitoringConfiguration

Describes configuration parameters for Amazon CloudWatch logging for a Managed Service for Apache Flink Studio notebook. For more information about CloudWatch logging, see Monitoring.

Contents

LogLevel

The verbosity of the CloudWatch Logs for an application.

Type: String

Valid Values: `INFO` | `WARN` | `ERROR` | `DEBUG`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinMonitoringConfigurationDescription

The monitoring configuration for Apache Zeppelin within a Managed Service for Apache Flink Studio notebook.

Contents

LogLevel

Describes the verbosity of the CloudWatch Logs for an application.

Type: String

Valid Values: `INFO` | `WARN` | `ERROR` | `DEBUG`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ZeppelinMonitoringConfigurationUpdate

Updates to the monitoring configuration for Apache Zeppelin within a Managed Service for Apache Flink Studio notebook.

Contents

LogLevelUpdate

Updates to the logging level for Apache Zeppelin within a Managed Service for Apache Flink Studio notebook.

Type: String

Valid Values: `INFO | WARN | ERROR | DEBUG`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3